



## Description

It is a new bright decorative LED light. Built-in LED cold light source, it can emit different colors as needed. It can be programmed to control multiple synchronous changes at random, enabling the full-color change effects such as synchronous colorful, jumping, scanning, and running water. It can also form a lattice screen with multi-point light sources and change various pictures, characters, animation effects, etc.

## **Features**

- \*Original appearance design, simple overall appearance, angular, exquisite and beautiful, structural waterproof design, waterproof grade IP65;
- \*High grayscale, high refresh, flicker-free and color design;
- \*Uniform and soft luminescence, no dark areas.
- \* Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.

## **Specifications**

Input voltage/power         DC24V/5W           Light source         EPISTAR/24PCS           Beam angle         120°           Color temperature         3000K (1900K, 2100K, 4000K, 5700K optional)           Light effect         ≥70lm/W           Color rendering index         Ra≥80           Color tolerance         SDCM≤5           Light source life         50000H           Control mode         ON/OFF           IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm           Net weight/gross weight         0.3kg/16kg(48PCS)	opoomoutiono	
Beam angle         120°           Color temperature         3000K (1900K, 2100K, 4000K, 5700K optional)           Light effect         ≥70lm/W           Color rendering index         Ra≥80           Color tolerance         SDCM≤5           Light source life         50000H           Control mode         ON/OFF           IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Input voltage/power	DC24V/5W
Color temperature         3000K (1900K, 2100K, 4000K, 5700K optional)           Light effect         ≥70lm/W           Color rendering index         Ra≥80           Color tolerance         SDCM≤5           Light source life         50000H           Control mode         ON/OFF           IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Light source	EPISTAR/24PCS
Light effect         ≥70lm/W           Color rendering index         Ra≥80           Color tolerance         SDCM≤5           Light source life         50000H           Control mode         ON/OFF           IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Beam angle	120°
Color rendering index         Ra≥80           Color tolerance         SDCM≤5           Light source life         50000H           Control mode         ON/OFF           IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Color temperature	3000K (1900K, 2100K, 4000K, 5700K optional)
Color tolerance         SDCM≤5           Light source life         50000H           Control mode         ON/OFF           IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Light effect	≥70lm/W
Light source life         50000H           Control mode         ON/OFF           IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Color rendering index	Ra≥80
Control mode         ON/OFF           IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Color tolerance	SDCM≤5
IK level         IK08           IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Light source life	50000H
IP level         IP65           Shell material         Aluminum + white PC cover           Appearance color         sand gray           Installation method         Screw fixed           Product size         122*94*54mm           Packing size         535*405*255mm	Control mode	ON/OFF
Shell material     Aluminum + white PC cover       Appearance color     sand gray       Installation method     Screw fixed       Product size     122*94*54mm       Packing size     535*405*255mm	IK level	IK08
Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	IP level	IP65
Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Shell material	Aluminum + white PC cover
Product size         122*94*54mm           Packing size         535*405*255mm	Appearance color	sand gray
<b>Packing size</b> 535*405*255mm	Installation method	Screw fixed
	Product size	122*94*54mm
Net weight/gross weight 0.3kg/16kg(48PCS)	Packing size	535*405*255mm
	Net weight/gross weight	0.3kg/16kg(48PCS)