

Description

It is a new bright decorative LED light. Built-in LED cold light source, it can emit different colors as needed. It can be programmed to control multiple synchronous changes at random, enabling the full-color change effects such as synchronous colorful, jumping, scanning, and running water. It can also form a lattice screen with multi-point light sources and change various pictures, characters, animation effects, etc.

Features

- *Original appearance design, simple overall appearance, angular, exquisite and beautiful, structural waterproof design, waterproof grade IP65;
- *High grayscale, high refresh, flicker-free and color design;
- *Uniform and soft luminescence, no dark areas.
- * Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.

Specifications

Input voltage/power DC24V/3W Light source EPISTAR/12PCS Beam angle 120° Color temperature RGB Light effect ≥20lm/W Color rendering index Ra≥60 Color tolerance SDCM≤5 Light source life 50000H Control mode DMX512 IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm Net weight/gross weight 0.35kg/19kg(48PCS)	Opcomouncilo	
Beam angle 120° Color temperature RGB Light effect ≥20lm/W Color rendering index Ra≥60 Color tolerance SDCM≤5 Light source life 50000H Control mode DMX512 IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Input voltage/power	DC24V/3W
Color temperature RGB Light effect ≥20lm/W Color rendering index Ra≥60 Color tolerance SDCM≤5 Light source life 50000H Control mode DMX512 IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Light source	EPISTAR/12PCS
Light effect ≥20lm/W Color rendering index Ra≥60 Color tolerance SDCM≤5 Light source life 50000H Control mode DMX512 IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Beam angle	120°
Color rendering index Ra≥60 Color tolerance SDCM≤5 Light source life 50000H Control mode DMX512 IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Color temperature	RGB
Color tolerance SDCM≤5 Light source life 50000H Control mode DMX512 IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Light effect	≥20lm/W
Light source life 50000H Control mode DMX512 IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Color rendering index	Ra≥60
Control mode DMX512 IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Color tolerance	SDCM≤5
IK level IK08 IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Light source life	50000H
IP level IP65 Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Control mode	DMX512
Shell material Aluminum + white PC cover Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	IK level	IK08
Appearance color sand gray Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	IP level	IP65
Installation method Screw fixed Product size 122*94*54mm Packing size 535*405*255mm	Shell material	Aluminum + white PC cover
Product size 122*94*54mm Packing size 535*405*255mm	Appearance color	sand gray
Packing size 535*405*255mm	Installation method	Screw fixed
	Product size	122*94*54mm
Net weight/gross weight 0.35kg/19kg(48PCS)	Packing size	535*405*255mm
	Net weight/gross weight	0.35kg/19kg(48PCS)