



### Feature:

- \* DMX512/1990 standard, a maximum of 1024 DMX control channels, and two photoelectric isolation signal output channels.
- \* Control a maximum of 96 computer lights or 96 dimming channels.
- \* Use the pearl lamp library (R20 lamp library), and support editing the lamp library on the console.
- \* The LCD display with backlight, and the display interface in Chinese and English.
- \* The built-in graph trajectory generator has 208 built-in graphs, which are convenient for users to control graphics trajectory of the computer lights, including circle, spiral, rainbow, chasing and other effects.
- \* Graphic parameters (such as amplitude, speed, interval, wave and direction) can be set independently, making it more convenient to design the desired shapes and scenes.
- \* Each scene can store 5 graphs; 10 graphs can be run at the same time.
- \* The scenes can be overlapped, and the graphs have width parameters, which can be programmed more quickly.
- \* With advanced marshalling function.
- \* It can store 60 materials, which can be set freely for material sharing or independent material.
- \* There are four material storage modes; material storage and invocation are more flexible and convenient.
- \* 60 playback scenarios can be stored for multi-step scenario and single-step scenario. Each multi-step scenario can store up to 600 scenarios.
- \* 10 playback scenarios can be output and run simultaneously.
- \* Equipped with 10 centralized fader; support button control and fader control.
- \* Support functions such as reconfiguration of section address codes, vertical and horizontal conversion, and reverse channel output, etc.
- \* Data can be kept in memory when shutdown or sudden power outage happens.
- \* U disk can backup console data and support re-importing data to console for use. Data in the console of the same model can be shared.
- \* Support remote software upgrade. You can add new functions anytime and anywhere.
- \* You can control the attributes of the computer light by preset fader, which is more convenient and fast.
- \* Support immediate black burst and scenarios interlocking.
- \* Professional gooseneck work light, suitable for indoor and outdoor performances (optional).

### Specifications:

Model	TL-SL703
Input voltage	AC 110-240V 50/60Hz
Fixture size (L×W×H)	500*460*120mm
Package size (L×W×H)	545*485*210mm
Gross weight	10.1kg
Net weight	7.6kg