

## **Description:**

It works with the built-in DANTE audio processor to form a set of high-end entertainment or conference professional sound system with outstanding human voice performance. It can be used as the main speaker or auxiliary speaker in various high-end conference rooms and multi-function halls, etc.

## Feature:

- \* Adopt a 12" mid-woofer and a 1.7" compressed tweeter.
  \* 15mm plywood housing, light weight, wear-resistant spray paint treatment and dust-proof net cotton inside.
  \* Precisely designed frequency divider optimizes the vocal MF performance.
- \* Built-in DANTE function of dual network ports can realize hand-in-hand connection.
- \* Support high-quality and long-distance signal transmission.

  \* The entire series is equipped with efficient high-power amplifier modules and powerful audio processors. Through different applications of the DANTE audio processor supporting system, it supports comprehensive parameter settings, including parameter equalization, frequency division, delay, and limit setting.

  \* Multiple screw hoisting holes, a pole socket with a diameter of 35mm, various installation methods.

## **Specification:**

Model	TS-612DT
Impedance	8Ω
Frequency response	50Hz-20KHz
Rated power	350W
Peak power	1400W
Sensitivity	99dB/W/M
Maximum SPL(rated/peak)	124dB/130dB
Coverage angle	(H)80° (V)60°
Tweeter	1.7" compressed tweeter ×1
Woofer	12" woofer ×1
Line input sensitivity	0dB
Network port	DANTE protocol
Bandwidth	1000M
Size	560×360×380mm (H×W×D)
Weight	22.5Kg
Power supply	AC 220V 50Hz
Power consumption	280W