



Moving Head Beam Light

TL-SL104



Feature:

- * Color panel: 14 color plate + 1 white light, bidirectional rainbow effect, and linear color mixing effect.
- * Fixed pattern panel: 12 fixed pattern plate + 1 white light, pattern dithering, one-way flow effect, adjustable speed, and arbitrary positioning function.
- * Rotating pattern panel: 8 rotating pattern plate + 1 white light, each pattern supports rotating in both directions, dithering and water flow effects.
- * Focusing: electronic ultra-smooth focusing.
- * Prism: 24-sided prism + 16-sided prism, the prism can be rotated in both directions and the speed is adjustable.
- * Strobe: the maximum stroboscopic speed is 20 times/sec, and random or pulse strobe is optional.
- * Atomization: 0-100% soft light effect.
- * Scan range: X-axis 540°/2.5 S, Y-axis 270°/1.5 S; resolution: 16Bit.
- * Display interface: a 2.8-inch widescreen LCD interface in Chinese and English that can be flipped; menu button supports the setting of over-temperature protection; by charging the mobile power supply through the MICRO USB port, the address code can be set, and no need to connect to the power supply.
- * Other function: the input signal has an isolation protection function to ensure stable signal transmission without interference; with intelligent high-temperature protection, the light is automatically turned off when the temperature is too high.

Specifications:

Model	TL-SL104
Input voltage	AC110V-240V 50/60Hz, 600W
Ballast	Electronic ballast
Light source	Philips FLEX series 380W
Average lifespan	6000H
Beam angle	2°
Control mode	DMX512 protocol, compatible with RDM function, support online program update
Channel	18 channels
Fixture material	High temperature resistant plastic + molded alloy material
Protection level	IP20
Fixture size (L×W×H)	389×267×688mm
Package size (L×W×H)	480×460×785mm
Gross weight	28.5kg
Net weight	25.5kg