



Feature

- * Color wheel: 7 color gels + white light, two-way stepless rotation, magnet positioning, color index, half-color and other functions.
- * Gobo wheel: 6 rotatable gobo wheels, 6 gobos; support pattern positioning, rotation, dithering, etc.
- * Dimming: 0-100% linear adjustment.
- * Strobe: electronic strobe, 0-25 times/sec (built-in pulse stroboscopic effect).
- * Focus: electric focus.
- * DMX512 port program update, convenient and fast software upgrade through DMX data cable.
- * Over-temperature protection function: built-in NTC temperature control function. When the LED is overheated, the output power will be intelligently reduced.
- * Full-color display, including the lamp usage time, software version number, reverse display of subtitle, etc.

Specification

| | |
|------------------------|---|
| Input voltage | AC 100-240V 50/60Hz, 800W |
| Light source | 650W White Light LED Module OSRAM Chip |
| Average lifespan | 50000H |
| Color temperature | 7500K |
| Beam angle | 45° (15°/30°/60° optional) |
| Control mode | Comply with the international standard DMX512 signal control protocol, 3-core (5-core optional) DMX512 signal interface; master-slave synchronous control mode, optional RDM function |
| Operation mode | DMX mode, user program mode, built-in program mode |
| Channel | 11 channels |
| Fixture material | High temperature resistant aluminum alloy/UV resistant engineering plastic + copper tube radiator + waterproof fan to assist heat dissipation |
| Protection class | Ip67 |
| Working temperature | -20°C~45 °C |
| Fixture size (L×W×H) | 346×267×476mm |
| Packaging size (L×W×H) | 405×355×565mm |
| Gross weight | 21.8KG |
| Net weight | 20.1KG |