



### Description:

It is mainly used for large-scale pixel screens on the exterior facade, walls, roofs and other places of the building. Through the changes of patterns and colors, the lights and the building merge into an integral whole, bringing the overall spectacular video expression and the linear outline decorative effects.

### Feature:

- \* Linear structure, ultra-light and ultra-narrow compact extruded aluminum lamp design, protective cover to ensure the transparency of the screen without affecting the lighting effect of the building and its interior.
- \* Using the connection method of the middle inlet and outlet double-ended male and female waterproof connectors.
- \* Seamless splicing, no color difference, 50 meters connection.
- \* Installed with simple fixed brackets or stainless steel clips.
- \* Customized surface treatment can be made according to customer needs to make it better integrated with the building.

### Specification:

|                              |                            |
|------------------------------|----------------------------|
| Model                        | TL-LH2502                  |
| Input voltage/power          | DC48V/8W                   |
| Number of LEDs/light sources | Sanan 5050/20PCS           |
| Beam angle                   | 120°                       |
| Housing color                | Grey                       |
| Color temperature            | RGB                        |
| Control mode                 | DMX512                     |
| Protection class             | IP67/IK06 Shock Protection |
| Certification                | CE/ROHS                    |
| Fixture size                 | 500*17*25mm                |
| Package size                 | 550*340*330mm (30PCS/box)  |
| Net weight/Gross weight      | 0.25kg                     |