



## Feature

\*SDIINPUTS (IN1~IN5): HD SDI video input port, supporting up to 1080p60 frame video signal;

\*SDIOUT (OUT1~OUT2): HD SDI video output port, capable of outputting up to 1080p60 frame video signals;

\*With CODE switch: baud rate and protocol control dial

\*2 485 control port, can cascade control 5 cameras, support Pelco\_D protocol and VISCA protocol cameras.

\*Through the CONFERENCE port or CONTROL port: communicate with the conference host to realize the camera tracking function

## Specification

|                            |  |
|----------------------------|--|
| Model                      | TF-0599                                    |
| Rate                       | automatic                                  |
| Operational Standards      | SMPTE259M; SMPTE292M; SMPTE424M            |
| Loss                       | <-15dB@1MHz~1.5GHz; <-10dB@1.5GHz~3GHz;    |
| Maximum rate               | 2.97Gbps                                   |
| Input and output levels    | 0.80Vp-p+/-10%                             |
| Input and output impedance | 75Ω  |
| Balance type               | Adaptive                                   |
| Maximum input distance     | 100 meters                                 |
| Power supply               | AC100-240V50~60HZ                          |
| Maximum power consumption  | 15W  |
| Weight                     | About 3Kg                                  |
| Dimensions (mm)            | 484*210*44                                 |
| Color                      | black                                      |
| Operating temperature      | -10°C ~ +60°C                              |
| Environment humidity       | 20%~80% relative humidity, no condensation |