



Description

Professional compact mixer, with ultra-low noise discrete microphone preamplifier and +48V phantom power supply; with 4 mono channels, 4 stereo input channels, built-in DSP effector. Suitable for all kinds of small and medium-sized conference venues, schools, enterprises and personal use.

Feature

- *The device supports 4-channel Mic input interface and is compatible with 4-channel line input interface. The microphone input interface has 48V phantom power.
- *The device supports 4 sets of stereo linear inputs and can be connected to stereo devices.
- *The device supports 3-band EQ for each mono input channel and has a peak LED indicator.
- *The device supports 1 set of stereo main output, 1 set of auxiliary output, 1 set of stereo monitor output, 1 headphone monitor output, and 1 set of CD/Tape output.
- *Built-in 24-bit DSP effects processor with 100 preset effects.

Specification

Frequency response	20Hz-20kHz (± 3 dB)
Distortion	<0.003% (A-weighted)
Phantom Power	+48V with switch
Microphone Input	4 (4 XLR ports)
Line Input	4 single-plug mono/stereo automatic switching hybrid interface
Stereo Input	4 (8 mono channels)
CD/Tape Input	1 CD/TAPE RCA stereo input interface
Output Path	1 stereo main output, 1 auxiliary output, 1 stereo monitor output, 1 headphone monitor output, 1 CD/Tape output
Effects	24-bit DSP effects (including vocal, small house, hall, echo, echo + reverb, plate, vocal plate, chorus GTR, rotary GTR, vibrato GTR types), 100 preset effects
Microphone input noise equalization	-119dB (A-weighted)
Common Mode Rejection Ratio	60dB
Single channel input gain	MIC : 0 to 48dB, LINE:-33 to+15dB; Stereo channel input gain : LINE : -8 to+6dB
Main Mix Crosstalk	-87dBu (A-weighted); Channel crosstalk : -85dBu (A-weighted)
Maximum output level	+20dBu
MIC input high pass filter	75Hz, 18dB/oct
Level Meter	2x4-dot pitch LED level indicator
Single channel equalization	High frequency : ± 15 dB@12KHz; Mid frequency : ± 12 dB@2.5KHz; Low frequency : ± 15 dB@80Hz
Equipment power supply	External AC18V/1A (AC 230-240V 50/60Hz) power adapter
Device power consumption	≤ 18 W
Product Size	Length 290.5×Width 292.9×Height 70mm
Product weight	1.9Kg