



Description:

The content management touch screen, by connecting to the content management system, controls the program and realizes the display and release of digital conference information such as texts and pictures.

Feature:

- * Support the display of conference information, multimedia information, promotional information, consulting information, advertising information, etc. The content, layout, theme and color of the display can be customized through the background.
- * Support scene interaction on the conference entrance screen, and synchronize the conference agenda to the entrance screen.
- * Support the entrance screen sign-in function; the initiator can send the conference sign-in QR code to the entrance screen.
- * Support conference information cache and offline playback functions.
- * Excellent anti-light interference ability.
- * Built-in high-performance SDIO interface WiFi module.
- * 1920×1080 HD display, high brightness and contrast, high-precision 10-point capacitive touch technology and sensitive response.

Specification:

Model	TR-0745
Operating system	Android8.1.0; support local USB upgrade
Display screen	15.6 inches
Resolution	1920*1080
Touch screen	G+G tempered glass capacitive screen, support 10-point touch
Contrast	1200:1
WIFI	IEEE802.11b/g/n
Brightness	≥250cd/m ² (typ.)
CPU	RK3288 Quad Core 1.8GHz Cortex-A17
RAM	2G
Memory	16G
Interface	USB2.0*2, HDMI*1, RJ45*1, DC12V*1, Earphone*1
Speaker	2W*2
Others	Support automatic power on/off
Bare metal size (W×D×H)	386.16×254.39×29mm
Ethernet	10M/100M/1000M adaptive Ethernet
TF card	Pop-up TF card socket, up to 128GB TF card
Video playback	Support mv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc.
Bluetooth	Optional
Power supply	Power adapter, 100V~240V, 50-60Hz; DC 12V-3A
Average current	<400mA
Rated power consumption	≤10W
Standby power	≤1W
Working temperature	0°C~50°C
Storage temperature	-10°C~50°C
Storage humidity	5%~90%RH
Working humidity	10%~90%RH
Maximum use time	18 hours/day
Frame color	Grey
Net weight (Kg)	2.6
Gross weight (Kg)	3.5
Static grade	Grade 3 (EN6100-4-22008) Contact discharge 6KV, air discharge 10KV