



Material: organic resin

## Note:

Due to the continuous product updating, the color and dimension of the products are subject to the actual product. The following specifications are for reference only.

## **Specifications:**

Model     T-4700       Rated power (100V)     7.5W, 15W       Rated power (70V)     3.8W, 7.5W       Impedance     Back:COM,White:1.3KΩ,Green:670Ω       Maximum power     30W       Speaker unit     95dB       Speaker unit     6.5"
Rated power (70V)     3.8W, 7.5W       Impedance     Black:COM,White:1.3KΩ,Green:670Ω       Maximum power     30W       Frequency response     80Hz -20KHz       Sensitivity     95dB       Speaker unit     6.5"
Impedance     Black:COM,White:1.3KΩ,Green:670Ω       Maximum power     30W       Frequency response     80Hz - 20KHz       Sensitivity     95dB       Speaker unit     6.5"
Maximum power 30W   Frequency response 80Hz -20KHz   Sensitivity 95dB   Speaker unit 6.5"
Frequency response     80Hz -20KHz       Sensitivity     95dB       Speaker unit     6.5"
Sensitivity 95dB   Speaker unit 6.5"
Speaker unit 6.5"
Protection level IP66
Installation size (mm) 345mm
Weight 8.32Kg
Unit (mm) H: 425