



## **Description:**

It works with the audio processor to form a set of high-end entertainment and conference professional sound system with outstanding vocal performance. It is suitable for various high-end conference rooms and multipurpose halls as the main speaker or auxiliary speaker.

## Feature:

- \* Adopt a mid-woofer and an annular polyethylene diaphragm compressed tweeter.
  \* 15mm birch housing, light weight, wear-resistant spray paint treatment, and dust-proof net cotton inside.
  \* The frequency divider in precise design is used to optimize the vocal MF performance.

- The entire series is equipped with efficient high-power amplifier modules.
   \* Multiple screw hoisting holes, a pole socket with a diameter of 35mm, various installation methods.
- \* 12"self powered
- \* 2 way full range \* 350 W RMS per speaker

## **Specification:**

| Model                  | TS-613P                    |
|------------------------|----------------------------|
| Impedance              | Ω                          |
| Frequency response     | 50Hz-20KHz                 |
| Rated power            | 350W                       |
| Peak power             | 1400W                      |
| Sensitivity            | 99dB/W/M                   |
| Max SPL(rated/peak)    | 124dB/130dB                |
| Coverage angle         | (H)100° (V)100°            |
| Tweeter                | 1.7" compressed tweeter ×1 |
| Woofer                 | 12" woofer ×1              |
| Line input sensitivity | OdB                        |
| Dimension (H×W×D)      | 560×360×380mm              |
| Weight                 | 21.8Kg                     |
| Power supply           | AC 220V 50Hz               |
| Power consumption      | 280W                       |