



### Description

Suitable for the sound reinforcement needs of small places such as multimedia classrooms, ordinary classrooms, conference rooms, training rooms, specialty stores, etc.

### Feature

- \*Supports 1 microphone and volume adjustment, 1 stereo line input and volume adjustment, and 1 stereo line output.
- \*Built-in mute function, microphone takes priority over line input.
- \*It comes with a 100V constant voltage input interface, which takes precedence over local broadcasts.
- \*Built-in HIFI high-fidelity high-end speakers, built-in electronic crossover, high and low independent amplifier driver.

### Specification

model	TF-20260H
Rated output power	≥2×25W (including main box and auxiliary box)
Output impedance	4-8Ω; frequency response : 40Hz~20KHz (≤±2dB)
Comes with 1 MIC volume adjustment and 1 AUX volume adjustment	
Input sensitivity	AUX IN : 350Mv±20MV/10KΩ; MIC : 5MV±0.5MV
signal-to-noise ratio	≥70dB; line output : ≥1V
harmonic distortion	≤1%
Operating temperature	5°C ~ 40°C; working humidity : 20% ~ 80% relative humidity, no condensation
Power consumption	≤60W, power supply voltage : ~ 220V 50Hz
Dimensions (W×H×D)mm	162×240×225
weight	7.5kg