




2 Channel Professional Amplifier

TF-22700C



Description

It is a new generation of high-power professional digital amplifier, which is characterized by high efficiency, stability and excellent sound quality. It has broken through the traditional technology in power technology, modulation technology and control technology, so as to substantially improve the overall performance. The application of variable oscillator modulation technology, multiple feedback control technology and innovative output power control technology endow the amplifier with over 95% ultra-high efficiency and excellent stability. And it is specially applicable to large-scale sound reinforcement venues, tour performance multipurpose halls, etc.

Feature

- * Support DC, short circuit, overload and overheat protection;
- * Designed with Signal (green), CLIP (orange), Fault (red), Power (blue) indicators on the panel;
- * Support XLR balanced input; SPEAKON audio socket output;
- * Support signal, power, temperature and other voltage limiting functions;
- * Support optional three modes: MONO/STEREO/BRIDGE;
- * Support optional 1V/2V sensitivity;
- * With a temperature-controlled fan, it rotates as soon as it is turned on; the fan accelerates as the temperature rises, and reaches full speed at about 60°C;
- * Super load capacity: support 8 ohms, 4 ohms, and minimum 2 ohms.

Specification

Model	TF-22700C
Output power (1KHz/THD≤1%)	Stereo 8Ω: 2*700W; Stereo 4Ω: 2*1200W; Stereo 2Ω: 2*1800W; Bridged 16Ω: 1400W; Bridged 8Ω: 2400W; Bridged 4Ω: 3600W;
Connector	XLR interface
Voltage gain (@1KHz)	37.5dB
Input sensitivity	2.2dBu(1V), 8.2dBu(2V)
Input impedance	10KΩ unbalanced, 20KΩ balanced
Frequency response (@1W power)	20-20KHz±1dB
THD+N (@1/8 power)	≤0.01%
SNR (A-weighted)	≥102dB
Damping coefficient (@1KHz)	≥200@ 8 ohms
Separation (@1KHz)	≥85dB
Protection method	Over-voltage protection, under-voltage protection, over-current protection, DC protection, short circuit protection
Indicator light	Power, Fault, Clip, Signal
Cooling method	Fan cooling
Power supply	~ 220 50Hz
Overall power consumption	600W
Dimension (L×W×H)	484×353×44mm
Weight	6.5kg

Notes: Output power: according to CEA-2006-B/CEA-490-A standard using 20ms pulse 1kHz sine wave measured under 1% total harmonic distortion. Overall power consumption: according to GB4943.1-2022 test method: measured under 1kHz sine wave rated load 1/8 power conditions.