



## Description

The professional-grade PC playback sound card comes with 2 audio-specific isolation transformers, which can electromagnetically isolate the ground potential noise at the computer end. It is characterized by low noise floor, stable operation, and pure sound quality, so as to protect the safety of equipment. It is suitable for live performances, theaters, musical instruments, pro band performances, engineering customization, etc.

## Feature

- \* With 2 XLR output interfaces, the volume can be adjusted individually.
- \* With a 6.35mm headphone output interface, the volume can be adjusted individually.

## Specification

<b>Model</b>	TF-P5GS
<b>Input</b>	1 USB 2.0 input
<b>Output</b>	2 XLR signal outputs, 1 6.35mm headphone output
<b>Operating system</b>	Windows XP or newer versions
<b>Drive program</b>	No need
<b>Sample rate</b>	32/44.1/48kHz
<b>Output end</b>	1x1/4" Stereo, 2xXLR
<b>Frequency response</b>	20Hz-20kHz (0/-0.5dB)
<b>Maximum output level</b>	0dBu
<b>Dynamic range</b>	100dB, A-weighted
<b>Working temperature</b>	10°-55°C
<b>Power consumption</b>	2.5W max
<b>Product size (L×H×D)</b>	81×52×121mm
<b>Package size (L×H×D)</b>	165×105×85mm
<b>Net weight</b>	0.4kg
<b>Gross weight</b>	0.5kg