



Full range speakers

KS-08AT



Description

- *It is a two-way passive speaker, defined by the highest quality music and language transmission, delicate and penetrating, and based on a multifunctional design, it can be used in multiple places .
- *It uses 1 8-inch mid-bass unit, 1 44mm tweeter and 2 8-inch passive radiation paper cones, which not only better suppresses nonlinear distortion, but also reduces its resonant frequency, allowing the speaker to obtain better bass diving depth when making sound .
- *KS-08AT uses customized bass drivers and passive panels, which have excellent electro-acoustic conversion efficiency. Compared with its peers, it can carry higher power and output stronger low-frequency energy .
- *The precisely designed passive crossover network effectively reduces frequency overlap, and the use of high-quality filtering components ensures that every note is reproduced clearly .
- *The 80°×60° coverage angle provides balanced sound field coverage for the entire acoustic space when installed horizontally or vertically .
- *Flexible mounting bracket and mounting method, easy for engineering installation .
- *Professional speaker sockets and plugs with good electrical characteristics .

Features

Used in small meeting rooms, conference halls, churches, etc. and various high-end application places.

Specification

Rated power	200W
Peak power	800W
Nominal impedance	8Ω
Frequency range (-10dB)	60Hz-20KHz
Sensitivity (±3dB)	96dB
Maximum sound pressure level (rated/peak)	119dB/125dB
Woofers	8" woofer × 1+2 × 8" passive radiation cone
Tweeter	44mm compression tweeter × 1
Coverage angle (-6dB)	80° (H) 60° (V)
Dimensions (H×W×D)	403×250×220(mm)
Net weight	6 kg