



Desktop dual screen paperless TS-8515

Embedded software: Paperless conference terminal client software V2.0



Description

The paperless conference terminal controller is equipped with the terminal embedded software to handle the file push, file distribution, browsing and reading, file annotation, smart sign-in, voting, electronic whiteboard, electronic nameplate, conference communication, conference service, video signal interconnection, conference control, same-screen broadcasting and other applications during the meeting process to meet the needs of various high-end conference occasions, as well as important government affairs, business, enterprises, institutions and large-scale event venues.

Feature

- *Adopt dual-screen paperless intelligent desktop terminal design, with an 11.6-inch auxiliary screen on the back and a seamless, back-panel-free connection, highlighting the high-end atmosphere of the product. It can display the patterns required for the meeting and the names of the meeting guests, perfectly realizing the powerful interactive paperless conference functions.
- *Adopt all-aluminum structure, high-quality aluminum materials plus CNC precision carving processing. The display frame and body are made of aluminum alloy CNC precision processing. The whole is made of aluminum alloy, making the equipment exquisite, light, beautiful and atmospheric.
- *The surface treatment of the equipment is anodized, with bright color. The high-definition screen is a well-known brand, using A-standard display screen, high resolution, bright and transparent colors.
- *Supports arbitrary switching between paperless meeting mode and Windows computer mode ; with 2 USB 3.0 interfaces, and can browse or upload files by connecting a USB flash drive.
- *Supports signal management permissions, can control the same-screen broadcast of any participant, and supports group same-screen broadcast.
- *Support adding account and password login function, can automatically log in to the default meeting, and can choose to participate in the desired meeting; with strong confidentiality performance and automatically clears local meeting files when the meeting ends.
- *The entire system adopts a 12V DC low-voltage power supply that complies with international safety standards, ensuring that it remains within the safe range for human contact during operation, effectively avoiding electrical safety hazards.
- *With manual adjustment of the screen angle function, allowing, allowing users to flexibly adjust the display to any angle between 0-45° according to actual needs and visual comfort.



Desktop dual screen paperless TS-8515

Embedded software: Paperless conference terminal client software V2.0

Specification

Main screen parameters

Main screen	Touch Support
CPU	i5 6300U
Cores/Threads	Dual core and four threads
Frequency	2.4 Ghz
Memory	DDR4 4G
Harddisk	Solid state 128G
Operating Voltage	12V
Elevation Angle	0-45°
Ambient temperature/humidity	-20°C ~ 50°C Humidity ≤ 70%
Main screen size	15.6 inches
Main screen ratio	16:9
Display size	344.16(W) × 193.59(H)mm
Main screen resolution	1920 × 1080 P
Backlight type	10S4P WLED, 15K hours, including LED driver
Main screen contrast	800:1
Main screen brightness	250cd/m ²
Power consumption	45 W
Viewing angle	IPS 85/85/85/85 (Typ.)
Signal system	EDP
USB3.0	2
Ethernet	10/100/1000M/bps
Operating temperature	0-50 °C
Product dimension	359.6 × 216.61 × 193.9 (mm)
Product weight	5.15 kg
Gross Weight	6.55 kg

Secondary screen parameters

Secondary screen size	11.6 inches
Secondary screen	No touch support
Secondary screen resolution	1366(RGB)×768 [W × GA]
Secondary screen contrast	1000 : 1
Secondary screen brightness	250 (Typ.)
Secondary screen working environment	Working temperature: 0 ~ 50 °C ; Storage temperature: -20 ~ 60 °C
Secondary screen operating frequency	60Hz
Secondary screen viewing angle	85/85/85/85 (Typ.)
Secondary screen type	IPS
Secondary screen voltage	3.3V
Display size	255(W) × 143(H)mm