

Conference Delegate Unit TS-0305A

Full digital conference system audio transmission embedded software V2.25



Feature

- * Adopt a 4.3-inch IPS full color touch screen with a user-friendly interface.
- * Adopt a short microphone pole and a high-sensitivity microphone core, support long-distance sound pickup.
- * Uncompressed audio transmission technology. The sampling rate is up to 48K, and it can provide perfect sound quality with a bandwidth of 80Hz-16KHz.
- * Adopt 100M network transmission, adopt network cable hand-in-hand connection, convenient for wiring.
- * Adopt standard TCP/IP communication protocol, and each unit can support ping packet function.
- * Simultaneous interpretation supports 63+1 channels, and support dual-channel listening function, listen to different interpreter channels at the same time.
- * With two 3.5mm headphone jacks, support listen to the sound of any one of 63+1 channels or connecting an external microphone.
- * With a built-in independent web server, support four language switching, adjustment of microphone ID number, microphone sensitivity, microphone EQ and other parameters.
- * Support the function of speech timekeeping and speech countdown. The delegate unit can apply for speaking.
- * Support internal feedback suppression function, voice control function, adjustable voice control sensitivity.
- * Support 5-band EQ adjustment function, adjust the sound effects according to the voice characteristics of different speaker to achieve the perfect effect.
- * Support (disk) clock display function. It can display the time, and synchronize server time.
- * Support the conference logistics service function, send service demand of tea, paper and pen, manual services and other custom demands to the conference server.
- * Support voting function. There are multiple voting mode options, and the content of the options can be customized and sent to the unit for display.
- * Support sign-in function. You can also disable and control the unit check-in, and other functions through the PC software.
- * Support firmware upgrade function on the web page.
- * Support the IP address sniffing function; the ID number, IP address and MAC address of unknown units

can be found by PC software.

Specification

Microphone type	TS-0305A
Microphone core directivity	Electret condenser microphone
Frequency response	Cardioid
Microphone input impedance	80Hz~16kHz
Sensitivity	1K Ω
Maximum SPL	-40 \pm 1dB (0dB=1V/Pa, at 1KHz)
Signal-to-noise ratio	120dB(THD<3%)
Crosstalk	>80dB(A)
Dynamic range	>70dB
THD	>80dB
Maximum power consumption	<0.3%
Power supply method	3.0W
Color	Conference host power supply
Dimensions (LxWxH)	Oxidized fine sand black
Microphone pole length	154.9 \times 99 \times 60.5mm(excluding microphone rod length)
Mounting method	240mm integrated square short microphone rod (light black)
Weight	Desktop type