



# Conference Microphone

## TS- 0324



### Description

The product features compact size, light weight, high definition, high sensitivity and low noise characteristics, providing users with a high-quality conference experience. At the same time, considering the need for convenient installation, it can be easily embedded in the desktop to provide a neat desktop layout.

### Feature

- \* All core components of the microphone use domestically produced chips, which are safe, confidential and controllable.
- \* Digital transmission link, connected to the cascade port of the conference server for power supply through the network port to six-pin aviation cable, uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth perfect sound quality.
- \* The conference PC software supports the function of timing and scheduled speech for the delegate unit. The conference PC software supports the function of timing speech for the chairman unit, and the speaking time is not limited .
- \* The chairman unit has a priority function, which can turn off the microphones of all delegate unit who are speaking.
- \* Support 5-band EQ adjustment function, adjust sound effects according to voice characteristics of different speakers until the perfect effect is achieved.
- \* Support WEB page control to adjust parameters such as microphone ID number and microphone sensitivity.
- \* Support PING packet function.
- \* Supports sign-in function, and can also prohibit unit sign-in, control unit sign-in and other functions through PC software.
- \* Supports web page firmware upgrade function.
- \* Support IP address sniffing function; the ID number, IP address, MAC address and other parameters of the unknown unit can be found through the PC tool.
- \* Support PC software microphone control, supports voice control function, and the voice control sensitivity is adjustable.

### Specification

Microphone Type	Electret condenser
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Microphone input impedance	680Ω
Sensitivity	-41± 1.5 dB (1KHz 0dB=1V/Pa)
Maximum SPL	120dB
SNR	>80dB(A)
Dynamic Range	>80dB
THD	<0.1%
Maximum power consumption	1W
Power supply	Conference host power supply
Network port	2, hand-in-hand cascade ports
Color	Space Gray
Sign-in function	Button sign-in
Dimensions (LxWxH)	48.8×57×139mm
Microphone rod length and color	409mm black (5-core cable)
Installation	Embedded
Weight	0.13KG