



Description

It is used in performance activities, stadiums, theaters, multipurpose halls and various high-end occasions.

Feature

- * The three-way coaxial listening speaker uses a 14-inch coaxial woofer and a 100mm+65mm imported neodymium coaxial mid-high compression driver.
- * The 14-inch three-way coaxial speaker design is used to concentrate the tweeter, mid-range and bass units at the same point for divergence.
- * The cabinet is made of high-quality imported birch wood, adopts precise CNC machining, polyurea spray paint, high-end and wear-resistant.
- * With hanging parts, it can realize the function of stage sound monitoring.
- * Support directional control with a wider frequency band; the 800-16KHz horizontal and vertical directions are controlled by the point sound source horn.
- * The polygonal cabinet structure supports adjustable monitoring angle.
- * Three-frequency single drive design.
- * Professional speaker sockets and plugs with good electrical characteristics.

Specification:

Model	KS-14F
Rated power	500W
Peak power	2000W
Nominal impedance	8Ω
Frequency range	60Hz-20KHz
Sensitivity	104dB(1M/1W)
Maximum SPL (rated/peak)	131dB/137dB
Woofer	14" woofer × 1
Tweeter	100mm+65mm coaxial mid-tweeter × 1
Coverage angle (-6dB)	75°(H) 40°(V)
Net weight	26kg
Dimension (H×W×D)	420×580×480mm