



Active Column Speaker

KS-12A25



Description

It is used in various mobile performances, small and medium-sized clubs , auditoriums, multi-function halls and various high-end application places.

Features

- *The cabinet adopts a dual-guided design, which can achieve a low-frequency response down to 38Hz and output a powerful bass effect . It is equipped with 8 2.3-inch mid- and high-frequency drivers to achieve high-definition seamless coverage, allowing listeners in different areas of the venue to be in the best listening position .
- *To support different user and environmental requirements, the signal input is equipped with 2-way XLR multi-function jacks and 1-way stereo RCA input, combined with Bluetooth audio streaming, which fully meets common connection methods , and additional balanced output ports are added to perfectly achieve cascading .
- *Supporting Bluetooth TWS technology, it can realize true wireless stereo, bringing a more convenient experience to users. There is no need to worry about cable constraints. It provides a freer and more convenient audio experience, and brings excellent stereo effects, making the sound more real and three-dimensional .
- *Built-in DSP processor , can achieve one-key low-frequency enhancement and one-key noise reduction functions through physical buttons .
- *Professionally designed aluminum alloy connecting rod and integrated wire assembly, easy one-handed carrying, worry-free installation, plug and play .

Specification

Type	Active portable column speaker
Rated power	400W+400W
Peak power	1600W+1600W
Crossover frequency	4th/200Hz, DSP electronic frequency division
Frequency range (-3dB)	38 Hz-20KHz
Input method	2-channel XLR multi-function jack input, 1-channel stereo RCA input, 1-channel Bluetooth input, 1-way XLR output
Functional support	Support low frequency enhancement, Bluetooth supports TWS, and supports one-key noise reduction
Maximum sound pressure level (rated/peak)	117 dB/123dB
Voltage input	AC 220V 50Hz-60Hz
Coverage	120° (H) 40° (V)
Low frequency speaker	12" × 1
Mid-high frequency speakers	2.3 " × 8
Net weight	17.5kg
Dimensions (H x W x D)	Bass: 560 × 350 × 430 (mm);Sound column: 597 × 96 × 103 (mm);Support rod: 800 × 35 × 50 (mm)
Total product height	2000 (mm)