



## IP Network Speaker T-8807B

### Embedded software: Digital IP network terminal embedded software V2.0



#### Description

IP network speakers. Suitable for listening test classrooms, conference rooms, hospital departments, high-speed rail lounges and other places. Used for local sound reinforcement and emergency broadcasting. At the same time, it can also play bell tasks or background music programs.

#### Feature

- \*The speaker is designed with high-density ABS material, which has the advantages of shockproof, durability, exquisite appearance, etc.
- \*It has 2-channel MIC input interfaces, one of which supports connecting a microphone to realize local paging and sound amplification functions and supports network volume adjustment; one of which can be connected to an external digital detector. The device has a built-in digital ambient sound detection algorithm to detect abnormal status of the playback speaker.
- \*Built-in microphone, supports audio detection, supports collecting and detecting audio frames, network packet loss rate, maximum frame spacing, link crossing points and other data, and analyzes playback status and audio recognition, and uploads it to the background, supports exporting reports.
- \*It has 1-channel line (AUX) input interface, supports network volume adjustment, supports local sound amplification function when disconnected from the network, and supports background accompaniment preset function.
- \*The wireless audio module can be expanded to realize local sound amplification with wireless microphone. The Bluetooth receiver can be expanded to receive Bluetooth audio for local sound amplification.
- \*It has 1-channel short-circuit input interface, which supports customized alarm triggering, local media library music playback, volume adjustment and other functions.
- \*It has 1-channel RS-485 interface and supports external volume control panel.
- \*The dual network interface design and the terminal support redundant backup function effectively avoid the problem of the device being unable to permanently connect to the system due to a single point of failure.
- \*It has a 100V constant voltage signal backup input interface, which switches to the backup channel when the machine is without network to avoid crosstalk between local signals and backup signals.
- \*Supports network and analog 100V main and standby switching functions. Supports automatic switching to the analog 100V constant voltage backup line when power is off or the network is disconnected. The delay of the hearing backup switching is less than 0.03 seconds. There is no delay, no lag, no dropout during the switching process, and it does not affect the normal broadcast; when the network and power supply return to normal, it automatically switches to the main channel. The switching time is less than 0.03 seconds. There is no delay, no lag, no dropout during the switching process, and it does not affect the normal broadcast.
- \*The main speaker has a built-in 2×30W (MAX) dual-channel Class D digital power amplifier, and one channel is connected to the sub-speaker, adopting a high and low frequency division design; the sound quality is delicate and the power is strong; it has a network volume setting.
- \*Built-in network audio decoding module, supports mainstream audio formats such as MP3, WAV, FLAC, OGG, AAC, OPUS, etc., and is compatible with the full sampling rate of 8kHz-48kHz.
- \*Built-in DSP audio processing, supports ultra-low latency digital mixing, and 10-band EQ equalization configuration.
- \*Built-in 3-level priority settings: (1) Network alarm signals take priority over local input signals and 100V analog backup. (2) The priority of local input signals MIC, AUX and network background music is configured by the server; local input signals MIC and AUX are mixed at the same level. (3) 100V analog backup signals have the lowest priority.
- \*Supports remote firmware upgrades and equipment maintenance via the network to reduce staff workload.
- \*The system adopts data redundancy encoding and decoding algorithm and supports anti-packet loss recovery function. The network packet loss is 37.5%, and the audio playback is smooth.



## IP Network Speaker T-8807B

### Embedded software: Digital IP network terminal embedded software V2.0

#### Specification

<b>Network interface</b>	Standard RJ45×2 input
<b>Transmission rate</b>	100Mbps
<b>Supported protocols</b>	TCP/IP, UDP, IGMP, ICMP
<b>Audio format</b>	Supports mainstream audio formats such as MP3, WAV, FLAC, OGG, AAC, OPUS, etc.
<b>Audio mode</b>	16-bit CD-quality sound
<b>Sampling rate</b>	8kHz-48kHz
<b>Auxiliary line input level</b>	350mV Industrial standard 3.81mm crimping terminal
<b>Frequency response</b>	80Hz-16kHz (+1dB/-3dB)
<b>MIC input sensitivity (unbalanced)</b>	120mV Industrial standard 3.81mm crimping terminal
<b>MIC frequency response</b>	200Hz-10kHz (+1dB/-3dB)
<b>Harmonic distortion</b>	≤1%
<b>Signal-to-Noise Ratio</b>	≥70dB
<b>Output power</b>	2×30W (MAX)
<b>Maximum sound pressure level</b>	99dB
<b>Sensitivity</b>	86dB
<b>Power consumption</b>	60W
<b>Short circuit input</b>	Dry contact input industrial standard 3.81mm crimping terminal
<b>Backup 100V input</b>	Industrial standard 5.08mm crimping terminal
<b>Working temperature</b>	5°C~40°C
<b>Working environment humidity</b>	20%~80% relative humidity, no condensation
<b>Input power</b>	~220V 50Hz
<b>Main box net weight</b>	2.8kg
<b>Net weight of auxiliary box</b>	2.4kg
<b>Dimensions (L x W x H)</b>	165×140.2×305mm