



Moving Head Light

TL-SL186



Feature

- * Color mixing system: CMY+CTO color mixing system, stepless changing color.
- * Color wheel: 6 colors + 1 white light.
- * Fixed gobo wheel: 9 gobos + 1 white light, adjustable speed, flexible positioning function.
- * Rotating gobo wheel: 7 replaceable gobos + white light, bidirectional rotation and positioning.
- * Effect pattern wheel: Effect wheel/Fire pattern/Water pattern, bidirectional rotation.
- * Focusing: Linearly adjustable focusing/infrared auto-focusing function.
- * Prism: Quadrangular prism, bidirectional rotation and positioning.
- * Zoom in: 11× zoom 5-55°.
- * Atomization: An atomization effect.
- ** Scanning range: X-axis 540°/2.7 S (optional 630°), Y-axis 270°/1.5 S, precise scanning and positioning.
- * Display interface: A wide-screen 2.8-inch LCD interface in Chinese and English, with rechargeable battery; you can enter the menu to set the address code and perform other settings without powering it on; the menu is hierarchically structured and has a friendly graphical interface.
- * Intelligent heat dissipation: Using wind direction drainage and temperature intelligent monitoring technology, built-in NTC temperature control function, when it is overheated, the output power of the LED is intelligently reduced.

Specification

Model	TL-SL186
Input voltage	AC110V-240V 50/60Hz, 800W
LED light source	600W
Average lifespan	50000H
Color temperature	6500K
Beam angle	5~55°
Control mode	DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface (DMX wireless function optional)
Channel	25/21CH
Fixture material	High temperature resistant plastic + molded alloy material
Protection class	Ip30
Fixture size (L×W×H)	427×276×807mm
Package size (L×W×H)	705×510×710mm
Gross weight	38.8kg
Net weight	33.3kg