



# Moving Head Beam Light

## TL-SL192



### Feature:

- \* Color mixing system: CMY+CTO color mixing system stepless color changing.
- \* Color wheel: 6 colors + 1 white light.
- \* Fixed gobo wheel: 9 gobos + 1 white light, adjustable speed, flexible positioning function.
- \* Rotating gobo wheel: 7 replaceable gobos + white light, bidirectional rotation and positioning.
- \* Effect gobo wheel: effect wheel/fire effect/water effect supports bidirectional rotation.
- \* Pattern cutting system: it can cut triangles, squares, parallelograms, semi-circles; the cutter pattern supports 90° rotation and any positioning function according to the scene.
- \* Focusing: linear adjustable focusing.
- \* Prism: a quadrangular prism, support bidirectional rotation and positioning.
- \* Zoom in: 11× zoom 5-55°.
- \* Atomization: two atomizations, support single-layer/double-layer atomization superimposition.
- \* \* Scanning range: X-axis 540°/2.7 S (optional 630°), Y-axis 270°/1.5 S, precise scanning and positioning.
- \* Display interface: a wide-screen 2.8-inch LCD interface in Chinese and English, with rechargeable battery, you can enter the menu to set the address code and perform other settings without powering on; the menu is hierarchically structured and has a friendly graphical interface.
- \* Intelligent heat dissipation: using wind direction drainage and temperature intelligent monitoring technology, built-in NTC temperature control function, when the LED is overheated, it will intelligently reduce the output power.
- \* Aperture function, zoom in and out dynamic effect.

### Specifications:

|                      |  |
|----------------------|--|
| Model                | TL- SL192  |
| Input voltage        | AC110V-240V 50/60Hz, 800W  |
| Light source         | 600W   |
| Average lifespan     | 50000H   |
| Color temperature    | 6500K  |
| Beam angle           | 5~53°  |
| Control mode         | DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface (DMX wireless function optional) |
| Channel              | 38/23 channels   |
| Fixture material     | High temperature plastic + molded alloy material   |
| Protection class     | IP30   |
| Fixture size (L×W×H) | 427×276×807mm  |
| Package size (L×W×H) | 705×510×710mm  |
| Gross weight         | 42kg   |
| Net weight           | 36.6kg   |