

## Description

This product is a small, feature- rich HDBaseT wall-embedded receiver box that supports HDMI video output, internal and external audio output, POC power supply, two-way transmission of infrared signals, pass-through EDID and built-in EDID functions, improving compatibility with different displays, and supporting a resolution of  $3840 \times 2160 \, P30Hz$ .

## **Feature**

- \*Equipped with 1-channel HDMI-A female interface output and 1-channel HDBaseT input;
- \*Supports HDMI1.4 standard and HDCP1.4 standard;
- $^{\star}$ The transmission resolution supports 3840×2160 P 30Hz, and the output video resolution is the same as the input resolution;
- \*Using advanced HDBaseT transmission technology, the video data is not compressed, high-definition, lossless and without delay;
- \*Supports P O C power supply, convenient for on-site installation and wiring;
- \*With power-off memory protection function and unique ESD static protection function;
- \*Equipped with 1-channel 3.5mm analog audio output interface, supporting simultaneous output of analog audio and HDMI embedded audio;
- \*Equipped with 1-channel infrared input interface and 1-channel infrared output interface, supporting infrared two-way transparent transmission;
- \*Resolution up to 3840×2160 P 30H z; HDPC: 3840×2160 P 30Hz\_24bit; HDTV: 3840×2160 P 30Hz\_24bit;
- \*Supports EDID management, optional pass-through EDID or built-in EDID.

## Specification

Video output	1 × HDMI digital video output interface
Video input	1 × HDBaseT input interface
LED indicator	1×Signal indicator light
Audio output	1 × 3.5mm analog audio output interface
Infrared	1× 3.5mm infrared input interface, 1× 3.5mm infrared output interface
HDMI input resolution	3840 × 2160 P 30Hz
HDMI transmission cable maximum	15m ( 1080P60Hz ) ; 10m (3840 × 2160P30Hz)
transmission distance	
The longest transmission distance of network	65m (1080P60Hz); 35m (3840×2160P30Hz)
cable transmission line	
Power supply	12V
Dimensions (L x W x H)	86×86×36.3mm
Rated power consumption	12w
Weight	270g
Ambient temperature	-10 °C—+45°C
Ambient humidity	10%-80%