



# Moving Head Beam Light

## TL-LT802



### Features

- \* Color: 1 color wheel, 16 colors + 1 white light.
- \* Fixed pattern: 18 fixed gobo wheel + 1 white light, with flow, index, and shaking functions.
- \* Focus: DMX linear focusing, ultra-fine and smooth focus adjustment.
- \* Prism (standard): eight prisms + four row lens, sixteen prisms, support variable-speed bidirectional rotation and superimposition.
- \* Strobe: Double-chip strobe 0.3-25 times/s, with synchronous, asynchronous and random strobe modes, and the speed is adjustable.
- \* Scanning range: X-axis 540°/4.5 S, Y-axis 270°/2.8 S, with automatic return function.
- \* Display interface: adopt widescreen 2.8-inch LCD interface in Chinese and English, with flip function;
- \* The input signal has isolation protection function to ensure stable signal transmission without interference.
- \* Support high temperature intelligent protection, automatically turn off the light if the temperature is too high;
- \* Support automatic power reduction of ballast in closed light state;
- \* Support software upgrade through DMX data cable;
- \* Support to display lamp usage time, bulb usage time and software version number.

### Specification

<b>Input voltage</b>	AC110V-240V 50/60Hz, 545W
<b>Ballast</b>	Electronic ballast
<b>Light source</b>	MSD/Silver/380W
<b>Average lifespan</b>	2000H
<b>Color temperature</b>	7800K±300K
<b>Beam angle</b>	2.5°
<b>Control mode</b>	DMX512 signal; support RDM protocol and program online update function (optional for DMX wireless function)
<b>Channel</b>	15/13 channels
<b>Fixture material</b>	High temperature engineering plastic + cast aluminum material
<b>Protection class</b>	Ip66
<b>Fixture size (L×W×H)</b>	477×320×724mm
<b>Packaging size (L×W×H)</b>	630×550×660mm
<b>Gross weight</b>	40kg
<b>Net weight</b>	34.5kg