

## Interactive Intelligent Flat Panel

## TV-X8175 (Specification TV-X75A custommized)



#### **Description**

itc HUB interactive intelligent flat panel focuses on small and medium-sized conference rooms to create a small conference center. The product integrates high-definition display, digital whiteboard, high-quality audio and other functions; equipped with Windows 10 IoT Enterprise Entry system, it meets the needs of conference presentation, writing, interaction, collaboration, sharing, video, data security, etc., covering the entire process of the meeting.

#### **Feature**

- \*The 75-inch DLED LCD screen has a Full HD 4K system icon display and a simple business-style design. The whole body is made of all-aluminum alloy with an aurora purple color. The ultra-narrow bezel design has a screen-to-body ratio of up to 90%, an ultra-thin screen, hidden ports, and a simple and elegant shape.
- \*Built-in non-independent computer module, all conference functions are run in the computer module, and the computer module uses the genuine and activated Windows 10 IoT operating system.
- \*The data files are encrypted using the national secret SM2 and SM3 encryption algorithms, and the encryption state is maintained during the transmission process to ensure the security and reliability of data transmission and storage; it complies with national security standards and enhances the overall information security protection capabilities.
- \*It has 12 pogo pin magnetic interfaces and can be paired with a detachable 48MP HD camera and 8-array microphone module. There is no need for separate wiring, and physical protection can be used to prevent the leakage of meeting information.
- \*Ultimate audio experience: The product adopts a 2.0-channel design with two sound chambers: 2×20W (mid-high frequency) gap-firing speakers; it has five sound effects options (standard, conference, vocal, music, cinema) to meet the needs of different scenarios.
- \*It has a Type-C full-function interface that can realize screen projection, reverse control, and audio and video signal transmission functions.
- \*It has an HDMI loop-out interface, a DP input interface, and supports 4K 60Hz.
- \*It has 1 RS232, 2 IO, and 2 RELAY IoT central control interfaces, which are convenient for integration and management with other devices, realize intelligent environmental control, and improve user experience and comfort.
- \*It has a built-in storage battery and supports abnormal power outage protection function. After an abnormal power outage, the internal battery is activated to automatically save meeting data and conference progress, and can continue to be used after power is turned on.
- \*With 85% NTSC high color gamut, the image display is clear, colorful and saturated, and the details of the picture are truly restored.
- \*It has a hardware-level blue light protection mechanism with a blue light ratio of less than 25%, which can effectively filter and reduce the radiation of high-energy short-wave blue light, enabling long-term viewing without fatigue and ensuring the health of users' eyes.
- \*The display uses high-precision touch technology, which can accurately identify touch objects with a diameter of 1.6 mm, ensuring a delicate operating experience.
- \*The entire screen and screen protection layer adopt zero-adhesion technology to effectively prevent light reflection.
- \*It is made of advanced anti-glare (AG) tempered glass material, which effectively suppresses ambient light interference and screen reflection, significantly reduces the visual discomfort caused by glare, ensures viewing comfort, and provides a softer visual experience.
- \*It supports multiple wake-up methods. In the screen-off state, you can wake up the device by picking up a pen, double-clicking the screen, or pressing a button. Picking up a pen to wake up allows you to quickly use the whiteboard and annotation functions.



#### Interactive Intelligent Flat Panel

### TV-X8175 (Specification TV-X75A custommized)

- \*It supports the use of a camera and sound pickup module to realize the voice assistant auxiliary function, and supports the operation of major functions through the voice assistant, such as: starting a meeting, ending a meeting, turning off the screen, shutting down the phone, etc.
- \*The document has a borderless design. When the user opens the document, it automatically enters the document presentation mode, and the document content will be displayed in full screen. During the document presentation, annotations, video playback, split-screen whiteboard, and image materials can be inserted to meet the needs of displaying more document content.
- \*It has the function of preparing a welcome interface before the meeting, you can add background audio, video, and pictures, and you can customize the welcome interface theme.
- \*It has a quick meeting mode to meet the needs of temporary meetings, multi-person discussions, brainstorming and other activities.
- \*It has quick voting and custom voting/scoring functions, and has voting and satisfaction evaluation templates; the voting methods are divided into QR code scanning voting and raising hands voting, and QR code scanning voting can choose anonymous voting and real-name voting, and voting/scoring can have custom options.
- \*It has the function of scanning code to sign in. You can sign and view it immediately during the meeting. After scanning the code to sign in, the name of the sign-in person will be displayed in real time.
- \*It has the function of conference screen recording, and supports the selection of 2K and 4K resolutions. It supports multiple ways of saving screen recordings, and can be taken away by scanning the code or saved locally, in the conference room, or in a USB flash drive.
- \*It supports multiple screen projection methods such as NFC touch transmission, wireless screen projection, wired screen projection, oneclick screen projection from a screen projector, etc. It supports mixed screen projection of mobile phones and computers, and supports up to four screens on the same screen; it supports reverse operations on the computer screen projection content.
- \*Supports application screen projection, for example, specifying browser screen projection, specifying document screen projection; other application messages will not pop up, and other tasks can be processed during the screen projection process to protect privacy.
- \*It supports mixed split-screen, and can display whiteboard, dynamic video, audio, documents, annotations and other pages at the same time during the meeting. It can display any split-screen in full screen or compare different solutions, and supports 4 split-screens.
- \*It supports uploading multiple file formats by scanning QR codes during the meeting, including MP4, MP3, PDF, WORD, XLSX, text, JPG, PNG, etc., which can be directly viewed and annotated.
- \*Supports whiteboard writing; supports inserting image materials into the whiteboard; supports multi-point writing; supports multiple erasing methods such as gesture erasing, sliding to clear the screen, circle eraser, pixel eraser, etc.; has infinite canvas and two-finger zoom function; supports multiple whiteboard file saving formats, and can save in PNG, PDF, WORD, PPT and other formats.
- \*The whiteboard supports OCR intelligent text recognition and graphic recognition functions, which can automatically convert written fonts and patterns into standard text and graphics.
- \*It supports full-channel annotation function, and you can choose a variety of annotation saving methods. You can scan the code to take it away or save it locally, in the meeting, or on a USB flash drive.
- \*Support PPT presentation countdown mode.
- \*It has the function of archiving files after the meeting. Attendance, voting results, and conference recordings can be saved locally or uploaded to the integrated management platform.
- \*It has a smart conference management platform that adopts a B/S architecture and supports login control software for operating systems such as Windows, Linux, MacOS, Android, and IOS to meet different on-site needs.
- \*The comprehensive management platform has multiple account permissions for ordinary users and administrators; the platform has a background data dashboard function, which can view the number of conference rooms, conference room usage, equipment online and offline status and user account status, and can count daily participants, daily meeting duration, daily number of meetings, daily active users, etc. on a monthly, weekly and daily basis, which facilitates statistical analysis and unified management without the need to configure a separate cloud platform.
- \*It has the function of creating meetings. You can reserve meeting rooms and meeting times in advance. After a successful reservation, the device homepage will display the day's meeting list in real time. The meeting list can view information such as the host and meeting time. You can set whether the meeting is encrypted and whether the data is allowed to be downloaded. You can set the storage time of historical meetings, which can be selected from 6 months, 12 months, or permanent.
- \*Supports web-based login to the management platform, where you can view unit meetings and historical meetings. Historical meetings display the meeting name, meeting booker, meeting number, meeting start time, and whether the video is recorded. You can view/export pre-meeting sign-in and voting results, and meeting recording videos.
- \*It has a meeting setting function, which can set whether the meeting files are encrypted. If file encryption is turned on, the meeting materials cannot be saved locally on the client and cannot be shared. After the meeting, the materials cannot be viewed locally and can only be viewed and downloaded through the background.



# Interactive Intelligent Flat Panel TV Y2475 (On self-setion TV Y754)

# TV-X8175 (Specification TV-X75A)

### **Specification**

System version	Processor	Intel i7 11th generation processor, maximum turbo frequency 4.10GHz
Season		
1508   1508	-	
Display size	-	
Screen highpy size   927.9H + 1649.6V     Physical resolution   3840 (H) + 260 (V)     Color   3850 (H) + 260 (V)     Col		
Physical resolution		
Color (Color 1.078(1081)           Screen brightness 280CD/m* (min.) 400CD/m*(typ.)           Contrast 1200.1(yp.) 5000-1 (min.) 400CD/m*(typ.)           Anti-blue light 3upport           Anti-blue light 3upport           Anti-glare 2000000000000000000000000000000000000		
Sorcen brightness		
Screen brightness   350CD/mr (min.) 400CD/mr(typ.)	5	
Contrast         1200:1(pyp.) 5000:1 (max)           Anti-glare         support           Display frame rate         600-2           Input Interface         1xLNE-N: 1xHIC-IN.1 (xLDP-IN; 1xVIDEO-IN (USB-C+reverse control); 1xLINE-N: 1xHID-IN.1 (xLDP-IN; 1xVIDEO-IN (USB-C+reverse control); 1xLINE-N: 1xHID-IN.1 (xLDP-IN; 1xVIDEO-IN (USB-C+reverse control); 1xLINE-N: 1xHID-IN; 1xLINE-N: 1xHID-IN; 1xVIDEO-IN (USB-C+reverse control); 1xLINE-N: 1xHID-IN; 1xVIDEO-IN (USB-C+REVEX)           Touch sensing technology         Infrared sensing touch recognition technology           Maximum number of linguity plotts         40 points           Response time         8m(xp.)           Writing height         2 other           Touch accuracy         1 he middle 90% touch area is a 1 mm           Touch accuracy         1 he middle 90% touch area is a 1 mm           Touch accuracy         1 he middle 90% touch area is a 1 mm           Touch diameter         3 ingle point 21 femm, multiple points 22mm           Glass specifications         3 ingle point 21 femm, multiple points 22mm           Writing Screen surface hardness         9 H           <	Color	1.07B(10bit)
Anti-blue light         support           Anti-glare         support           Display fame rate         00H2           Input interface         1×LAN; 1×TOUCH; 1+HDM-IN; 1×DP-IN; 1×VIDEO-IN (USB-C+reverse control); 1×LAN; 1×IDEO-IN (USB-C+REVEX); 1×IDEO-IN (USB-C-REVEX); 1×IDEO-IN (USB-C-REVEX); 1×IDEO-IN (USB-C-REVEX); 1×IDEO-IN (USB-	Screen brightness	350CD/m² ( min. ) 400CD/m²(typ.)
Anti-glare   Support	Contrast	1200:1(typ.) 5000:1 ( max )
Input interface	Anti-blue light	support
National	Anti-glare	support
Output Interface         1.4LINE-INL. 1.5MLC-IN. 4.4USB-A; 1.4RS232; 24IO; 2.4RELAY;           Output Interface         1.4LINE-IOUT; 1.4LINE-OUT;           Touch sensing technology         Infrared sensing touch recognition technology           Touch output form         HID Standard           Maximum number of Input points         40 points           Response time         8ms(typ.)           Writing method         Finger, stylus, or other opaque objects           Writing height         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         2.0mm           Theoretical clicks         Unlimited           Touch diameter         Single point ±1.6mm, multiple points ±2mm           Glass specifications         3.2mm tempered glass           Writing screen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         2.88%           Color temperature (source)         Min.8000K:Types500K:Max.11500K           Interpolation resolution         3.2768 × 32768           Operating voltage         DC 545%           Wiffe? 46Hz/56Hz           Bluetooth         Bluesooth 5.2           Operating voltage         2.0Mm/26Hz/56Hz           Standard po	Display frame rate	60Hz
Output Interface         1.H.D.H.O.UT, T.K.I.N.EO.UT.           Touch ensing technology         Infrared sensing touch recognition technology           Touch output form         40 points           Response time         8ms(typ.)           Writing method         Finger, stylus, or other opaque objects           Writing height         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Fhoeretical clicks         Unlimited           Glass specifications         3.2mm tempered glass           Writing scens surface hardness         9 H           Glass haze         3% 8%           Visible light transmittance         288%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         C 5v45%           Four supply         90-264 × 50/60HZ input           Standard power consumption         460W           Standard power consumption         400W           Standard power consumption         400W           Standard power consumption         400W           Storage temperature         • 0°C + 40°C           Operating attitude         90% 80%	Input interface	1×LAN; 1×TOUCH; 1×HDMI-IN; 1×DP-IN; 1×VIDEO-IN (USB-C+reverse control);
Touch sansing technology         Infrared sensing touch recognition technology           Touch output form         HID Standard           Maximum number of input points         40 points           Response time         8ms(yp.)           Writing height         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Theoretical clicks         Unlimited           Touch diameder         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mm tempered glass           Writing screen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         ≥85%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32788 × 22788           Touch screen power         \$2.5W           WiFit         WiFit2.44H/25Hz           Bluetooth         Bluetooth 5.2           Power supply         90-284Y-59(6HZ input           Standard power consumption         < 460W		1×LINE-IN; 1×MIC-IN; 4×USB-A; 1×RS232; 2×IO; 2×RELAY;
Touch output form         HID Standard           Maximum number of input points         40 points           Response time         8ms(typ.)           Writing method         Finger, stylus, or other opaque objects           Writing method         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Theoretical cloks         Unlimited           Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mm tempered glass           Writing screen surface hardness         9H           Writing screen surface hardness         9H           Wrisible light transmittance         ≥88%           Visible light transmittance         ≥88%           Color temperature (source)         Min. 8000K/1ype9500K/Max.11500K           Interpolation resolution         32788 × 3278           Operating voltage         D C 5V45%           Touch screen power         42.5W           WiFi         WiFi62-46Hz/5GHz           Bluetooth         2.0mm           Power supply         9.2647–50/60HZ input           Standard power consumption         4.05W           Standard power consumption         4.05W	Output Interface	1×HDMI-OUT; 1×LINE-OUT;
Touch output form         HID Standard           Maximum number of input points         40 points           Response time         8ms(typ.)           Writing method         Finger, stylus, or other opaque objects           Writing method         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Theoretical cloks         Unlimited           Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mm tempered glass           Writing screen surface hardness         9H           Writing screen surface hardness         9H           Wrisible light transmittance         ≥88%           Visible light transmittance         ≥88%           Color temperature (source)         Min. 8000K/1ype9500K/Max.11500K           Interpolation resolution         32788 × 3278           Operating voltage         D C 5V45%           Touch screen power         42.5W           WiFi         WiFi62-46Hz/5GHz           Bluetooth         2.0mm           Power supply         9.2647–50/60HZ input           Standard power consumption         4.05W           Standard power consumption         4.05W	Touch sensing technology	
Maximum number of input points         40 points           Response time         8ms(typ.)           Writing height         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Touch accuracy         In middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass haze         3%-8%           Writing screen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         > 288%           Color temperature (source)         Min. 8000KT, type 9500K; Max. 11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC 5V±5%           Operating voltage         DC 5V±5%           WiFi         WiFi62 4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power suply         90-2647~50/60Hz input           Standard power consumption         <460W           Standard power consumption         <460W           Maximum sound power         2.0 Channels           Maximum sound power         2.0 Channels           Storage tempera		
Response time         8ms(typ.)           Writing method         Finger, sylus, or other opaque objects           Writing height         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Theoretical clicks         Unlimited           Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mt tempered glass           Writing screen surface hardness         9H           Glass haze         3%-9%           Visible light transmittance         ≥88%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC 5945%           Touch screen power         42.5W           WiFi         WiFi62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-2847-50/60HZ input           Standard power consumption         4.05W           Standard power consumption         4.05W           Standard power consumption         4.05W           Storage temperature         1.07C-160°C           Storage temperature         0.0C-4.0°C           Operating hu		40 points
Writing method         Finger, stylus, or other opaque objects           Writing height         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Theoretical clicks         Unlimited           Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mm tempered glass           Writing acreen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         ≥88%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32788 × 32768           Operating voltage         DC 5v±5%           Touch screen power         25.5W           WIFI         WiFl62.4GHz/SGHz           Bluetooth         Bluetooth 5.2           Power supply         90-284V-50/60HZ input           Standby power consumption         ≤460W           Standby power consumption         ≤0.5W           Audio channels         2.0 Channels           Maximum sound power         ≥20W @ 60           Storage temperature         -10°C-60°C           Operating humidity         0%-60%RH, non-condensing		·
Writing height         2.0mm           Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Theoretical clicks         Unlimited           Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mm tempered glass           Writing screen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         ≥88%           Color temperature (source)         Min. 8000K;Type9500K;Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC 5V±5%           Touch screen power         ≤2.5W           WiFig         WiFie2.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-264V~50/6GHZ input           Standard power consumption         <460W           Audio channels         2.0 Channels           Audio channels         2.0 Channels           Storage temperature         10°C~+60°C           Storage humidity         10%-69%RH, non-condensing           Operating temperature         0°C~+40°C           Operating glimperature         0°C~+40°C           Operating glimperature	·	
Touch accuracy         The middle 90% touch area is ±1mm           Two-point recognition distance         > 20mm           Theoretical clicks         Unlimited           Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mm tempered glass           Writing screen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         288%           Color temperature (source)         Min. 8000K:Type9500K:Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC SV±5%           Touch screen power         42.5W           WiFi         WiFi62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-2847-50/60HZ input           Standard power consumption         <460W	-	
Two-point recognition distance		
Theoretical clicks         Unlimited           Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mm tempered glass           Writing screen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         288%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC 5V±5%           Touch screen power         \$2.5W           WiFi         WiFi62_4GHz/5GHz           Bluetooth         \$2.0W           Power supply         90-264V-50/60HZ input           Standard power consumption         \$460W           Standby power consumption         \$460W           Standby power consumption         \$0.5W           Audio channels         \$2.0 Channels           Maximum sound power         \$2.20W @ 60           Storage temperature         \$10°C-80°C           Storage temperature         \$20°C-40°C           Operating humidity         \$20%-80%RH, non-condensing           Operating altitude         \$5000m           Bare metal dimensions (length x thickness x height)         \$17.3mm x 88.7mm x 1011.4mm	-	
Touch diameter         Single point ≥1.6mm, multiple points ≥2mm           Glass specifications         3.2mm tempered glass           Writing screen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         288%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32768 x 92768           Operating voltage         DC 5V±5%           Touch screen power         42.5W           WiFI         WiFi62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-264V-50/60HZ input           Standard power consumption         <0.5W           Standard power consumption         <0.5W           Audio channels         2.0 Channels           Maximum sound power         2×20W @ 60           Storage temperature         -10°C+40°C           Operating themperature         0°C-40°C           Operating themperature         0°C-40°C           Operating thempidity         0%-80%RH, non-condensing           Operating humidity         0%-80%RH, non-condensing           Operating humidity         0%-80%RH, non-condensing           Operating humidity         0%-80%RH, non-condensing		
Glass specifications   3.2mm tempered glass		
Writing screen surface hardness         9H           Glass haze         3%-8%           Visible light transmittance         288%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC 5V±5%           Touch screen power         ≤2.5W           WiFi         WiFi62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-264V-50/60HZ input           Standard power consumption         ≤460W           Standard power consumption         <0.5W           Audio channels         2.0 Channels           Maximum sound power         ≥220W @ 6Q           Storage temperature         -10°C-+60°C           Storage humidity         10%-80%RH, non-condensing           Operating themperature         0°C-+40°C           Operating thirtude         ≤5000m           Bare metal dimensions (length x thickness x height)         1900mm x 225mm x 1125mm           Display size         1649.6mm x 927.9mm           Display size         1649.6mm x 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg		
Glass haze         3%-8%           Visible light transmittance         ≥88%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC 5V±5%           Touch screen power         ≤2.5W           WiFi         WiFi62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-264V~50/60HZ input           Standard power consumption         ≤460W           Standby power consumption         <0.5W           Audio channels         2.0 Channels           Maximum sound power         ≥2.20W @ 6Ω           Storage temperature         10°C~+60°C           Storage humidity         10%-80%RH, non-condensing           Operating temperature         0°C~+40°C           Operating altitude         ≤500m           Sare metal dimensions (length x thickness x height)         1717.3mm × 82.7mm × 1011.4mm           Packing size (length x thickness x height)         1900mm × 225mm × 1125mm           Display size         1649.6mm × 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg           Shell color		
Visible light transmittance         ≥88%           Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC 5½±5%           Touch screen power         \$2.5W           WiFI         WiFI62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-264V-50/60HZ input           Standard power consumption         \$460W           Standard power consumption         <0.5W		
Color temperature (source)         Min.8000K;Type9500K;Max.11500K           Interpolation resolution         32768 × 32768           Operating voltage         DC 5V±5%           Touch screen power         ≤2.5W           WiFi         WiFi62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-264V−50/60HZ input           Standard power consumption         ≤460W           Standby power consumption         <0.5W           Audio channels         2.0 Channels           Maximum sound power         2×20W @ 6Q           Storage temperature         -10°C−460°C           Storage tumldity         10%−80%RH, non-condensing           Operating temperature         0°C−440°C           Operating altitude         ≤5000m           Bare metal dimensions (length x thickness x height)         1717.3mm × 88.7mm × 1011.4mm           Packing size (length x thickness x height)         1900mm × 225mm × 1125mm           Display size         1649.6mm × 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg           Shell color         Aluminum profile/sheet metal           Wall mounting holes (VESA): 4-M8 screw holes         800mmx400mm		
Interpolation resolution   32768 × 32768     Operating voltage   DC 5½5%     Touch screen power   ≤2.5W     WiFi   WiFi62.4GHz/5GHz     Bluetooth   Bluetooth 5.2     Power supply   90-264V-50/60HZ input     Standard power consumption   ≤460W     Standard power consumption   ≤0.5W     Audio channels   2.0 Channels     Maximum sound power   2×20W @ 6Ω     Storage temperature   −10°C−+60°C     Storage temperature   0°C−+40°C     Storage humidity   10%−80%RH, non-condensing     Operating temperature   0°C−+40°C     Operating humidity   20%−80%RH, non-condensing     Operating altitude   ≤5000m     Bare metal dimensions (length x thickness x height)   1717.3mm × 88.7mm × 1011.4mm     Packing size (length x thickness x height)   1900mm × 225mm × 1125mm     Display size   1649.6mm × 927.9mm     Thickness   88.7mm     Net weight   58.32kg     Gross weight   69.19kg     Shell color   silver gray     Housing material   Aluminum profile/sheet metal     Wall mounting holes (VESA): 4-M8 screw holes   800mm×400mm     Service life   50,000hrs(min.)	_	
Operating voltage         DC 5V±5%           Touch screen power         ≤2.5W           WiFi         WiFi62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-264V~50/60HZ input           Standard power consumption         ≤460W           Standby power consumption         <0.5W           Audio channels         2.0 Channels           Maximum sound power         ≥2×20W @ 6Ω           Storage temperature         -10*C~+60*C           Storage humidity         10%~80%RH, non-condensing           Operating temperature         0°C~+40*°C           Operating lumidity         20%~80%RH, non-condensing           Operating altitude         ≤5000m           Bare metal dimensions (length x thickness x height)         1717.3mm × 88.7mm × 1011.4mm           Packing size (length x thickness x height)         190mm × 225mm × 1125mm           Display size         1649.6mm × 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg           Shell color         4luminum profile/sheet metal           Housing material         Aluminum profile/sheet metal           Wall mounting holes (VESA): 4-M8 screw holes         800mm×400mm <t< th=""><th></th><th>**</th></t<>		**
Touch screen power ≤2.5W  WiFi WiFi6 WiFi62.4GHz/5GHz  Bluetooth Bluetooth 5.2  Power supply 90-264V~50/60HZ input  Standard power consumption ≤460W  Audio channels 2.0 Channels  Maximum sound power 2×20W @ 6Ω  Storage temperature -10°C~+60°C  Storage humidity 10%−80%RH, non-condensing  Operating temperature 0°C~+40°C  Operating altitude ≤5000m  Bare metal dimensions (length x thickness x height) 1717.3mm × 88.7mm × 1011.4mm  Packing size (length x thickness x height) 1900mm × 225mm × 1125mm  Display size 1649.6mm × 927.9mm  Thickness 88.7mm  Net weight 58.32kg  Gross weight 69.19kg  Shell color  Housing material Aluminum profile/sheet metal  Wall mounting holes (VESA): 4-M8 screw holes 800mmx400mm  Service life 50.000hrs(min.)		
WiFi         WiFi62.4GHz/5GHz           Bluetooth         Bluetooth 5.2           Power supply         90-264V~50/60HZ input           Standby power consumption         ≤460W           Standby power consumption         <0.5W		
Bluetooth         Bluetooth 5.2           Power supply         90-264V~50/60HZ input           Standard power consumption         ≤460W           Standby power consumption         <0.5W		
Power supply         90-264V~50/60HZ input           Standard power consumption         ≤460W           Audio channels         2.0 Channels           Maximum sound power         2×20W @ 6Ω           Storage temperature         -10°C−+60°C           Storage humidity         10%~80%RH, non-condensing           Operating temperature         0°C−+40°C           Operating altitude         ≤5000m           Bare metal dimensions (length x thickness x height)         1717.3mm × 88.7mm × 1011.4mm           Packing size (length x thickness x height)         1900mm × 225mm × 1125mm           Display size         1649.6mm × 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg           Shell color         silver gray           Housing material         Aluminum profile/sheet metal           Wall mounting holes (VESA): 4-M8 screw holes         800mmx400mm           Service life         50,000hrs(min.)		
Standard power consumption         ≤460W           Standby power consumption         <0.5W           Audio channels         2.0 Channels           Maximum sound power         2×20W @ 6Ω           Storage temperature         -10°C−+60°C           Storage humidity         10%−80%RH, non-condensing           Operating temperature         0°C−+40°C           Operating humidity         20%~80%RH, non-condensing           Operating altitude         ≤5000m           Bare metal dimensions (length x thickness x height)         1717.3mm × 88.7mm × 1011.4mm           Packing size (length x thickness x height)         1900mm × 225mm × 1125mm           Display size         1649.6mm × 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg           Shell color         silver gray           Housing material         Aluminum profile/sheet metal           Wall mounting holes (VESA): 4-M8 screw holes         800mmx400mm           Service life         50,000hrs(min.)	Bluetooth	
Standby power consumption         < 0.5W           Audio channels         2.0 Channels           Maximum sound power         2×20W @ 6Ω           Storage temperature         -10°C~+60°C           Storage humidity         10%~80%RH, non-condensing           Operating temperature         0°C~+40°C           Operating humidity         20%~80%RH, non-condensing           Operating altitude         ≤5000m           Bare metal dimensions (length x thickness x height)         1717.3mm × 88.7mm × 1011.4mm           Packing size (length x thickness x height)         1900mm × 225mm × 1125mm           Display size         1649.6mm × 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg           Shell color         silver gray           Housing material         Aluminum profile/sheet metal           Wall mounting holes (VESA): 4-M8 screw holes         800mmx400mm           Service life         50,000hrs(min.)	Power supply	90-264V~50/60HZ input
Audio channels       2.0 Channels         Maximum sound power       2×20W @ 6Ω         Storage temperature       -10°C~+60°C         Storage humidity       10%~80%RH, non-condensing         Operating temperature       0°C~+40°C         Operating humidity       20%~80%RH, non-condensing         Operating altitude       ≤5000m         Bare metal dimensions (length x thickness x height)       1717.3mm × 88.7mm × 1011.4mm         Packing size (length x thickness x height)       1900mm × 225mm × 1125mm         Display size       1649.6mm × 927.9mm         Thickness       88.7mm         Net weight       58.32kg         Gross weight       69.19kg         Shell color       silver gray         Housing material       Aluminum profile/sheet metal         Wall mounting holes (VESA): 4-M8 screw holes       800mmx400mm         Service life       50,000hrs(min.)	Standard power consumption	≤460W
Maximum sound power         2×20W @ 6Ω           Storage temperature         -10°C~+60°C           Storage humidity         10%~80%RH, non-condensing           Operating temperature         0°C~+40°C           Operating altitude         ≤5000m           Bare metal dimensions (length x thickness x height)         1717.3mm × 88.7mm × 1011.4mm           Packing size (length x thickness x height)         1900mm × 225mm × 1125mm           Display size         1649.6mm × 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg           Shell color         silver gray           Housing material         Aluminum profile/sheet metal           Wall mounting holes (VESA): 4-M8 screw holes         800mmx400mm           Service life         50,000hrs(min.)	Standby power consumption	< 0.5W
Storage temperature 10°C~+60°C  Storage humidity  10%~80%RH, non-condensing  Operating temperature  0°C~+40°C  Operating humidity  20%~80%RH, non-condensing  Operating altitude  \$5000m  Bare metal dimensions (length x thickness x height)  Packing size (length x thickness x height)  1717.3mm × 88.7mm × 1011.4mm  Packing size (length x thickness x height)  1900mm × 225mm × 1125mm  Display size  1649.6mm × 927.9mm  Thickness  88.7mm  Net weight  58.32kg  Gross weight  Shell color  Housing material  Wall mounting holes (VESA): 4-M8 screw holes  Service life  -10°C~+60°C  10%~80%RH, non-condensing  1717.3mm × 88.7mm × 1011.4mm  1717.3mm × 88.7mm × 1011.4mm  1719.3mm × 88.7mm × 1011.4mm  17	Audio channels	2.0 Channels
Storage humidity       10%-80%RH, non-condensing         Operating temperature       0°C~+40°C         Operating humidity       20%-80%RH, non-condensing         Operating altitude       ≤5000m         Bare metal dimensions (length x thickness x height)       1717.3mm × 88.7mm × 1011.4mm         Packing size (length x thickness x height)       1900mm × 225mm × 1125mm         Display size       1649.6mm × 927.9mm         Thickness       88.7mm         Net weight       58.32kg         Gross weight       69.19kg         Shell color       silver gray         Housing material       Aluminum profile/sheet metal         Wall mounting holes (VESA): 4-M8 screw holes       800mmx400mm         Service life       50,000hrs(min.)	Maximum sound power	2×20W @ 6Ω
Operating temperature 0°C~+40°C Operating humidity 20%~80%RH, non-condensing Operating altitude ≤5000m  Bare metal dimensions (length x thickness x height) 1717.3mm × 88.7mm × 1011.4mm Packing size (length x thickness x height) 1900mm × 225mm × 1125mm  Display size 1649.6mm × 927.9mm Thickness 88.7mm Net weight 58.32kg Gross weight 69.19kg Shell color silver gray Housing material Aluminum profile/sheet metal Wall mounting holes (VESA): 4-M8 screw holes 800mmx400mm Service life 50,000hrs(min.)	Storage temperature	-10°C~+60°C
Operating humidity       20%~80%RH, non-condensing         Operating altitude       ≤5000m         Bare metal dimensions (length x thickness x height)       1717.3mm × 88.7mm × 1011.4mm         Packing size (length x thickness x height)       1900mm × 225mm × 1125mm         Display size       1649.6mm × 927.9mm         Thickness       88.7mm         Net weight       58.32kg         Gross weight       69.19kg         Shell color       silver gray         Housing material       Aluminum profile/sheet metal         Wall mounting holes (VESA): 4-M8 screw holes       800mmx400mm         Service life       50,000hrs(min.)	Storage humidity	10%~80%RH, non-condensing
Operating altitude       ≤5000m         Bare metal dimensions (length x thickness x height)       1717.3mm × 88.7mm × 1011.4mm         Packing size (length x thickness x height)       1900mm × 225mm × 1125mm         Display size       1649.6mm × 927.9mm         Thickness       88.7mm         Net weight       58.32kg         Gross weight       69.19kg         Shell color       silver gray         Housing material       Aluminum profile/sheet metal         Wall mounting holes (VESA): 4-M8 screw holes       800mmx400mm         Service life       50,000hrs(min.)	Operating temperature	0°C~+40°C
Bare metal dimensions (length x thickness x height)  Packing size (length x thickness x height)  Display size  1649.6mm × 927.9mm  Thickness  88.7mm  Net weight  58.32kg  Gross weight  59.19kg  Shell color  Housing material  Wall mounting holes (VESA): 4-M8 screw holes  Service life  1717.3mm × 88.7mm × 1011.4mm  1900mm × 225mm × 1125mm  1649.6mm × 927.9mm  1649.6	Operating humidity	20%~80%RH, non-condensing
Packing size (length x thickness x height)1900mm × 225mm × 1125mmDisplay size1649.6mm × 927.9mmThickness88.7mmNet weight58.32kgGross weight69.19kgShell colorsilver grayHousing materialAluminum profile/sheet metalWall mounting holes (VESA): 4-M8 screw holes800mmx400mmService life50,000hrs(min.)	Operating altitude	≤5000m
Display size         1649.6mm × 927.9mm           Thickness         88.7mm           Net weight         58.32kg           Gross weight         69.19kg           Shell color         silver gray           Housing material         Aluminum profile/sheet metal           Wall mounting holes (VESA): 4-M8 screw holes         800mmx400mm           Service life         50,000hrs(min.)	Bare metal dimensions (length x thickness x height)	1717.3mm × 88.7mm × 1011.4mm
Thickness 88.7mm  Net weight 58.32kg  Gross weight 69.19kg  Shell color silver gray  Housing material Aluminum profile/sheet metal  Wall mounting holes (VESA): 4-M8 screw holes 800mmx400mm  Service life 50,000hrs(min.)	Packing size (length x thickness x height)	1900mm × 225mm × 1125mm
Net weight       58.32kg         Gross weight       69.19kg         Shell color       silver gray         Housing material       Aluminum profile/sheet metal         Wall mounting holes (VESA): 4-M8 screw holes       800mmx400mm         Service life       50,000hrs(min.)	Display size	1649.6mm × 927.9mm
Gross weight 69.19kg Shell color silver gray Housing material Aluminum profile/sheet metal Wall mounting holes (VESA): 4-M8 screw holes 800mmx400mm Service life 50,000hrs(min.)	Thickness	88.7mm
Shell color silver gray  Housing material Aluminum profile/sheet metal  Wall mounting holes (VESA): 4-M8 screw holes 800mmx400mm  Service life 50,000hrs(min.)	Net weight	58.32kg
Shell color silver gray  Housing material Aluminum profile/sheet metal  Wall mounting holes (VESA): 4-M8 screw holes 800mmx400mm  Service life 50,000hrs(min.)	Gross weight	69.19kg
Housing material  Wall mounting holes (VESA): 4-M8 screw holes  Service life  Aluminum profile/sheet metal  800mmx400mm  50,000hrs(min.)	•	silver gray
Wall mounting holes (VESA): 4-M8 screw holes  Service life  800mmx400mm  50,000hrs(min.)		Aluminum profile/sheet metal
Service life 50,000hrs(min.)		
To Hours X 7 days		
	Duration of use	10 110 at 0 x 1 days