



Feature:

- * Color wheel: 7 color gels + white light, two-way stepless rotation, magnet positioning, color index, half-color and other functions.
- * Gobo wheel: 6 rotatable gobo wheels, 6 gobos; support pattern positioning, rotation, dithering, etc.
- * Dimming: 0-100% linear adjustment.
- * Strobe: electronic strobe, 0-25 times/sec (built-in pulse stroboscopic effect).
- * Focus: electric focus.
- * DMX512 port program update, convenient and fast software upgrade through DMX data cable.
- * Over-temperature protection function: built-in NTC temperature control function. When the LED is overheated, the output power will be intelligently reduced.
- * Full-color display, including the lamp usage time, software version number, reverse display of subtitle, etc.

Specifications:

Input voltage	AC 100-240V 50/60Hz, 380W
Light source	300W White Light LED Module OSRAM Chip
Average lifespan	50000H
Color temperature	7500K
Light spot angle	45° (15°/30°/60° optional)
Control mode	Comply with the international standard DMX512 signal control protocol, 3-core (5-core optional) DMX512 signal interface;
Operation mode	master-slave synchronous control mode, optional RDM function DMX mode, user program mode, built-in program mode
Channel	9 channels
Fixture material	High temperature resistant aluminum alloy/UV resistant engineering plastic + copper tube radiator + waterproof fan to assist heat dissipation
Protection class	IP67
Working temperature	-20℃~45℃
Fixture size (L×W×H)	346×267×432mm
Packaging size (L×W×H)	405×355×515mm
Gross weight	17.1KG
Net weight	15.4KG