



Horizontal network intelligent interactive flat panel

TH-3255CX



Description

The horizontal intelligent interactive flat panel is used in medical and nursing places, and is generally installed in the lobby or aisle area. Support for inquiries, guides, missions, etc.

Feature

- * Support the display of hospital information and related missions.
- * Support querying the schedule of experts and doctors in each department.
- * Support 3D map for route navigation.
- * Support background remote upgrade.
- * Support timing switch on and off and restart the device, restart the software, remotely adjust the volume function, and upgrade the software.
- * Support log viewing function.
- * Support the replacement of display templates, which can be customized and modified according to the site environment.

Specification

Screen size	55 inches
Resolution	1920*1080
Screen ratio	16:9
Brightness	350cd/m ²
Contrast	1200:1
Viewing angle	178°
Refresh rate	120HZ
Touch	Support infrared 20-point touch
Backlight life	50000Hrs
Glass hardness	Explosion-proof tempered glass, Mohs hardness scale 7
Processor	Quad-core 1.8GHz main frequency
Memory	2GB DDR4
Hard disk	16GB
Operating system	Android7.0 or above
Built-in speaker	5W*2(8Ω)
Device interface	USB*2; HDMI*1; 3.5mm*1; TF card slot*1; Rs232*1
Network input (10/100M)	RJ45*1



Horizontal network intelligent interactive flat panel

TH-3255CX

2.4G WIFI	Support
Input power	100-240V
Operating power consumption	≤180W
Standby power consumption	≤0.5W
Operating temperature	-10 ~ 50°C
Working humidity	10% ~ 80%, relative humidity, no condensation
Size (L×H×D)	1257.80×728.60×66.80mm (excluding base)
Wall hole	Horizontal 400×Vertical 400
Net weight	49.2kg (including base)