



# Queuing ticket dispenser

## TH-3232ZZ



## Description

The Windows queuing ticket dispenser is placed in the hospital lobby, which is suitable for medical scenarios, and is used for patient registration, number collection, self-service payment, etc.

## Feature

- \* Support electronic medical insurance certificate, medical card, medical insurance card, ID card, medical record number and other ways to register and take the number.
- \* Support user WeChat public account (small program) to make an appointment for registration, and to pick up the number at the self-service machine.
- \* Support self-service appointment registration, number pickup and cancellation of appointment.
- \* Support self-service settlement and payment for medical technology and medicine collection.
- \* Support same-day registration and appointment to pick up the number.
- \* Support self-service nucleic acid billing.

## Specification

Screen size	32"
Resolution	1920*1080
Response time	8ms
Screen ratio	16:9
Brightness	260cd/m <sup>2</sup>
Contrast	700:1
Viewing angle	Horizontal 130°, Vertical 110°
Refresh rate	120HZ
Touch	Support infrared 20-point touch
Glass hardness	Explosion-proof tempered glass, Mohs hardness scale 7
CPU	Quad core and quad thread, 3.20GHz
Running memory	4GB
System memory	240G SSD
Operating system	Windows 10
Built-in speaker	5W*2
Device interface	RS-232×6, USB port×8
Network input (10/100M)	Rj45×1
2.4G WIFI	support



## Queuing ticket dispenser

### TH-3232ZZ

<b>Social security card reader</b>	Reserved installation port
<b>Medical card reader</b>	Reserved installation port
<b>Receipt printing module</b>	Panel type RS-232 interface, thermal printing, automatic paper cutting (half cut), paper end alarm, paper near end alarm, paper jam alarm, black mark detection, printing width: 80mm, paper roll diameter: 80mm.
<b>Metal encrypted keyboard</b>	16-key metal (anti-riot, waterproof) encryption keyboard, passed the test of the bank card testing center, standard RS-232 interface, dedicated hardware encryption chip, and supports DES/3DES hardware encryption.
<b>Barcode scanner</b>	Support mobile phone or paper one-dimensional code, QR code recognition.
<b>Second generation ID card reader</b>	This device is a second-generation ID card verifier, which complies with the ISO 14443 Type B standard and uses wireless transmission to read out the personal information in the ID card.
<b>Input power</b>	100-240V
<b>Operating power consumption</b>	< 180W
<b>Standby power consumption</b>	< 0.5W
<b>Operating temperature</b>	-10 ~ 50°C
<b>Working humidity</b>	10% ~ 80%, relative humidity, no condensation
<b>Size (L×W×H)</b>	509×525×1795mm
<b>Net weight</b>	44kg