



## Description

The secondary triage screen is placed at the door of the consultation room or at the inspection window. It is suitable for medical scenarios, displays doctor information and patient queuing information, and supports calling number playback.

## Feature

- \* Support the display of information about doctors in the current consultation room, including doctor photos, names, titles, and profiles.
- \* Support the display of patient information, including current patient information, next patient information, and waiting patient information.
- \* Support displaying promotional slogans at the bottom of the screen, and the content of slogans can be modified through background software.
- \* Support background remote upgrade.
- \* Support the privacy protection of the patient's name, and display the patient's name with "\*" when displaying, such as Zhang\*, Huang\*yi.
- \* Support call reminder, the patient who is called will give a special reminder, and support voice broadcast.
- \* Support the background adjustment of the voice volume of the device calling number, and can take remote screenshots of the display interface.
- \* Support setting any time period for timing switch.
- \* Support log viewing function.
- \* Support the replacement of display templates, which can be customized and modified according to the site environment.

## Specification

|                         |  |
|-------------------------|--|
| Screen size             | 21.5 inches  |
| Resolution              | 1920*1080  |
| Screen ratio            | 16:9   |
| Brightness              | 250cd/m <sup>2</sup>   |
| Contrast                | 1200:1   |
| Viewing angle           | 178°   |
| Backlight life          | 50000Hrs   |
| Glass hardness          | Explosion-proof tempered glass, Mohs hardness scale 7            |
| CPU                     | Quad-core, the main frequency is 1.8GHz                          |
| Running memory          | 2GB DDR4   |
| System memory           | 32GB   |
| Android version         | Android 11   |
| Built-in speaker        | 3W*2(8Ω)   |
| Device interface        | USB3.0×2; HDMI×1; 3.5mm audio output interface×1; TF card slot×1 |
| Network input (10/100M) | RJ45×1   |
| 2.4G WIFI               | Support  |
| Input power             | 100-240V   |



## Triage screen

### TH-3221FZ

|                             |   |
|-----------------------------|---|
| Operating power consumption | ≤28W  |
| Standby power consumption   | ≤0.5W   |
| Operating temperature       | 0 ~ 40°C                                      |
| Working humidity            | 20% ~ 85%, relative humidity, no condensation |
| Size (L×H×D)                | 305×28.8×508.4mm                              |
| Wall hole                   | Horizontal 180×Vertical 308                   |
| Net weight                  | 5kg   |