



Description

The secondary triage screen is placed at the entrance of the clinic or at the examination window. It is suitable for medical scenarios. It displays the doctor information and patient queue information and supports number calling playback.

Features

- *Supports displaying the information of the doctor currently sitting in the clinic, including the doctor's photo, name, title, and brief introduction.
- *Supports display of patient information, including current patient information, next patient information, and patient waiting in line information.
- *It supports displaying promotional slogans at the bottom of the screen, and the slogan content can be modified through the background software.
- *Support background remote upgrade.
- *Supports privacy protection of patient names, and displays patient names with an asterisk (*), such as Zhang*, Huang*yi.
- *It supports call number prompts. Patients whose numbers are called will receive special prompts, and voice broadcasts are supported.
- *The background supports adjusting the volume of the device's calling voice and taking remote screenshots of the display interface.
- *Support setting any time period for scheduled power on and off.
- *Support log viewing function.
- *Supports replacement of display templates, and can customize template styles according to the on-site environment.



Specification

Screen size	15.6 inches
Resolution	1920×1080
Screen ratio	16:9
Display size	344.16 (H) × 193.59 (V)
Brightness	250 cd/ m ²
Contrast	1200:1
Viewing angle	178°
Backlight life	50000Hrs
Glass hardness	Explosion-proof tempered glass, Mohs 7 hardness
Processor	Quad-core, main frequency 2.0GHz
Running memory	2 GB DDR4
System memory	32 GB
Operating system	Android 11
Built-in speaker	3W *2(8Ω)
Device interface	USB2.0×2; HDMI×1; 3.5mm×1; TF card slot×1
Network input (10/100M)	Rj45×1
2.4G WIFI	support
Power supply mode	100-240V
Operating power consumption	≤ 50 W
Standby power consumption	≤0.5W
Operating temperature	0 ~ 40°C
Operating humidity	20% ~ 85%RH, no condensation
Overall dimensions (W×D×H)	236.3 × 25.8 × 376.3mm
Operating temperature	0 ~ 40°C
Wall-mounted holes	130 × 260mm
Net weight	4.6kg