



Features

- *Dimming: 0-100% electronic linear dimming, jitter-free smooth dimming technology.
- *Strobe: 0-25 times/second electronic strobe, adjustable speed, built-in random strobe or pulse strobe.
- *Color wheel: 7 colors + 1 white light, adjustable speed, arbitrary positioning function.
- *Fixed gobo wheel: 8 fixed patterns + 1 white light, adjustable speed, arbitrary positioning function.
- *Prism: 1 18-prism, can rotate forward and reverse, adjustable speed, arbitrary positioning function.
- *Display interface: Digital tube display, equipped with 4 mechanical buttons.
- *Temperature protection: Built-in NTC temperature control function, when the LED is overheated, the output power of the LED is intelligently reduced.
- *Scanning range: X-axis 540° (16-bit precision scanning) electronic error correction, Y-axis 172° (16-bit precision scanning) electronic error correction, precise scanning positioning, signal feedback, absolute position memory.



Specification

Input voltage	AC 110-240V, 50/60Hz
Rated power	150W
Power factor	PF≥0.90
light source	120W White LED
Average life of light source	50000H
Color temperature	9000K
Beam angle	2.8°
Control method	DMX512 protocol, built-in self-propelled mode, master-slave mode, voice control mode, manual control mode
Channel mode	Lite mode 10CH, standard mode 14CH
Housing material	V0 flame retardant ABS
Power interface	1 power input interface
Signal interface	1 RJ45 network input interface, 1 RJ45 network output interface
Operating temperature	-10°C ~ 45°C
Protection level	Ip20
Product size (L×W×H)	178×178×340mm
Packing size (L×W×H)	367×265×233mm(carton)
Gross weight of packaging	4.75kg
Product net weight	4.1kg