



# LED Studio Light

## TL-SK6301



### Features

- \*Optical system: Made of high-temperature resistant and high-transmittance optical glass (3-layer coating),  $\phi 140\text{mm}$  Fresnel lens.
- \*Dimming: 0-100% electronic linear dimming, jitter-free smooth dimming technology.
- \*Strobe: 0-25 times/second electronic strobe, speed adjustable, built-in random strobe or pulse strobe.
- \*Focusing: Linear electric focusing.
- \*Color mixing system: Warm white + cool white 2 colors can be linearly mixed to adjust the color temperature.
- \*Display interface: 1.5-inch blue screen LCD display; equipped with 3 manual knobs.

### Specification

Input voltage	AC 110-240V, 50/60Hz
Rated power	220W
Power factor	PF $\geq$ 0.98
Light source	200W LED (CW+WW)
Average lifespan of light source	50000H
Color temperature	2700K-6500K
Color tolerance	SDCM $\leq$ 3
Luminous flux	5016lm
Color rendering index	Ra $\geq$ 97
Beam angle	15°-65°
Control method	DMX512 protocol, RDM protocol, built-in master-slave mode, manual control mode
Channel mode	Standard mode 4CH
Housing material	die-cast aluminum
Power interface	1 power input interface, 1 power output interface
Signal interface	1 DMX512 input interface, 1 DMX512 output interface
Working environment temperature	-10°C-45°C
Protection level	Ip20
Product dimensions (L×W×H)	570×285×435mm
Packing dimensions (L×W×H)	610×335×395mm (carton)
Gross weight of packaging	13Kg
Product net weight	10.9Kg