



## Moving Head Beam Light

### TF-LT1821



## Features

- \*Dimming: 0-100% linear dimming
- \*Strobe: 0-25 times/second electronic strobe, adjustable speed
- \*Color mixing system: RGBW color mixing system, full light range dimming, smooth and uniform
- \*Macro function: preset multiple color macro functions
- \*Focusing: 0-100% linear electric focusing
- \*Zoom: 1-14 times linear electric zoom
- \*Effect: smooth focusing, rainbow effect, circle control effect, large focusing range, wide dyeing area
- \*Display: 1.8-inch TFT LCD display, 180-degree rotatable, Chinese and English switchable
- \*Horizontal: 54 0°, accuracy 2.11°/step, fine-tuning accuracy 0.008°
- \*Vertical: 270°, accuracy 0.86°/step, fine-tuning accuracy 0.0034°
- \*Photoelectric reset system: can accurately and automatically correct the X-axis/Y-axis position
- \*Cooling system: low-noise and high-efficiency fan cooling system
- \*Power interface: 1 power input interface, 1 power output interface
- \*Signal interface: 1 DMX512 input interface, 1 DMX512 output interface
- \*Standard accessories: 1 power cord, 1 signal cord, 2 sets of quick locks + bridge



## Moving Head Beam Light

### TF-LT1821

#### Specification

<b>Input voltage</b>	AC110V-240V , 50/60Hz
<b>Rated power</b>	720W
<b>Light source</b>	19*40W RGBW LED
<b>Average life of light source</b>	50000H
<b>Color temperature</b>	2000K-10000K
<b>Color rendering index</b>	Ra≥80
<b>Beam angle</b>	3.5°-50°
<b>Control method</b>	DMX512, self-propelled, master-slave, manual, supports RDM
<b>Channel mode</b>	21/23/35/78/92/97/99CH
<b>Shell material</b>	Die-cast aluminum
<b>Working environment temperature</b>	-20°C ~ 45°C
<b>Protection level</b>	IP65
<b>Product size (L×W×H)</b>	410×280×530mm
<b>Packaging size (L×W×H)</b>	670×510×340mm(carton)
<b>Packaging gross weight</b>	25.8kg
<b>Product net weight</b>	22.6kg