



Active Speaker

TF-GS1SO



Features

1. Active portable speaker column. Built-in DSP processor, enabling one-button low-frequency boost and one-button noise reduction via physical buttons.
2. Maximum sound pressure level (rated/peak): 117dB/123dB.
3. Voltage input: AC 220V 50Hz-60Hz.
4. Applicable to various mobile performance activities, small and medium-sized clubs, auditoriums, multi-functional halls and various high-end application venues.
5. Professionally designed aluminum alloy connecting rod and integrated wire assembly, allowing for easy one-handed carrying, worry-free installation, and plug-and-play functionality.
6. Frequency range (-3dB): 38Hz-20KHz.
7. Supports Bluetooth TWS.
8. Input methods: 2-channel XLR multi-function jack input, 1-channel stereo RCA input, 1-channel Bluetooth input, and 1-channel XLR output.

Specification

Low-frequency speaker	12" x 1
Mid-high frequency loudspeakers	2.3" x 8"
Power	Rated 400W + 400W; Peak 1600W + 1600W
Frequency division	4th/200Hz, DSP electronic frequency division
Coverage range	120° (H) 40° (V)
Net weight	17.5kg
Dimensions (H×W×D)	Bass 560×350×430 (mm); Speaker Post 597×96×103 (mm); Support Rod 1015×35×50 (mm)
Total product height	2000 (mm)