



Features

1. Preheat time: 4.0 minutes.
2. Heater type: Aluminum heating.
3. Oil tank capacity: 4.0 liters.
4. Output levels/adjustment range: 1%–100%.
5. Smoke output: 754 m³/min.
6. Spray distance: 6 meters.
7. Fuel consumption: 7 min/L
8. Continuous output time (100% output): 30 seconds.
9. Smoke emission angle: Adjustable from 0° to 130°.
10. Display interface: Features a blue-backlit LCD screen with 6 mechanical buttons; supports seamless switching between Chinese and English.
11. Temperature control system: Equipped with both mechanical and electronic temperature control.

Specification

Input voltage	AC 220-240V, 50/60Hz
Rated power	1500W
Power factor	PF≥0.95
Fuse	10A/250V
Working current	6.5A
Control method	DMX512 protocol, RDM control, manual control, remote control.
Channel mode	Standard mode 2CH
Shell material	Cold-rolled sheet
Power interface	1 power input interface
Signal interface	1 DMX512 input interface, 1 DMX512 output interface, 1 wireless input interface
Work environment temperature	-10°C ~ 45°C
Protection class	Ip20
Product dimensions (L×W×H)	528×397×316mm
Packaging dimensions (L×W×H)	615×430×340mm (carton)
Packaging gross weight	18.0kg
Product net weight	16.0kg