



Features

1. Optical system: Adopts high-temperature resistant and high-transmittance optical glass lens set (3-layer coating), with a $\phi 44\text{mm}$ aperture output lens.
2. Dimming: 0-100% electronic linear dimming with jitter-free smooth dimming technology.
3. Strobe: 0-25 times per second electronic strobe with adjustable speed, built-in random strobe or pulse strobe.
4. Features: Equipped with one input and one output daisy-chain power cable and signal cable (each 1.5 meters long), improving on-site lighting installation efficiency.
5. Pattern framing system: 4 independent manual framing shutters, adjustable at any angle to shape the light beam.
6. Display interface: LCD display with 4 mechanical buttons.

Specification

Input voltage	AC 110-240V, 50/60Hz
Rated power	100W
Power factor	PF $\geq$ 0.98
Light source	100W white light LED COB
Color temperature	3200K
Color tolerance	SDCM $\leq$ 3
Luminous flux	1100 lm
CRI	Ra $\geq$ 80
Beam angle	19°
Control mode	DMX512 protocol, with built-in Master-slave mode, Manual control mode
Channel mode	Standard mode 2CH
Casing material	Die-cast aluminum
Power connector	1 power input connector
Signal connector	1 DMX512 input connector, 1 DMX512 output connector
Operating temperature	-10°C ~ 45°C
IP rating	Ip20
Product dimensions (L×W×H)	390×190×135mm
Package dimensions (L×W×H)	480×240×190mm (carton)
Package gross weight	3.1kg
Product net weight	2.6kg