



Features

1. Dimming: 0-100% electronic linear dimming with jitter-free smooth dimming technology.
2. Strobe: 0-25 times per second electronic strobe with adjustable speed, built-in random strobe or pulse strobe.
3. Color mixing system: Warm white and cool white, 2 colors with linear color mixing for color temperature adjustment.
4. Tilt angle: 0°-60° motorized linear adjustable.
5. Features: High luminous efficiency, uniform light mixing, good heat dissipation with fin-type heatsink, stable performance.
6. Display interface: Digital tube display with 4 mechanical buttons.
7. Temperature protection: Built-in NTC temperature detection function, intelligently reduces the LED output power when the LED operates over temperature.

Specification

Input voltage	AC 110-240V, 50/60Hz
Rated power	50W
Power factor	PF≥0.90
Light source	48*0.5W LED (WW24+CW24)
Average LED lifespan	50000H
Color temperature	3200K-6500K
Color tolerance	SDCM≤3
Luminous flux	3365 lm
CRI	Ra≥95
Beam angle	105°
Control mode	DMX512 protocol, with built-in Master-slave mode, Manual control mode
Channel mode	Compact mode 3CH, Standard mode 6CH
Casing material	Die-cast aluminum + iron
Power connector	1 power input connector
Signal connector	1 DMX512 input connector, 1 DMX512 output connector
Operating temperature	-10°C~45°C
IP rating	Ip30
Opening size	560×145mm
Product dimensions (L×W×H)	580×160×91mm
Package dimensions (L×W×H)	635×230×165mm (carton)
Package gross weight	5.3kg
Product net weight	4.9kg