



## Features

1. Dimming: 0-100% electronic linear dimming with jitter-free smooth dimming technology.
2. Strobe: 0-25 times per second electronic strobe with adjustable speed, built-in random strobe or pulse strobe.
3. Color mixing system: RGBW (red, green, blue, white) linear color mixing; 16.8 million colors (0-100% saturation adjustable).
4. Laser system: 0.1W single green laser starry sky effect with auto-rotation function.
5. Lens wheel: Motorized rotation with adjustable speed and positioning function, supports infinite forward and reverse rotation.
6. Display interface: Digital tube display with 4 mechanical buttons.
7. Temperature protection: Built-in NTC temperature detection function, intelligently reduces the LED output power when the LED operates over temperature.

## Specification

|                            |                                                                                                         |
|----------------------------|---------------------------------------------------------------------------------------------------------|
| Input voltage              | AC 110-240V, 50/60Hz                                                                                    |
| Rated power                | 100W                                                                                                    |
| Power factor               | PF≥0.90                                                                                                 |
| Light source 1             | 6*15W RGBW 4-in-1 LED                                                                                   |
| Light source 2             | 100mW semiconductor solid-state laser, wavelength 520nm                                                 |
| Average LED lifespan       | 50000H                                                                                                  |
| Control method             | DMX512 protocol, with built-in Auto run mode, Master-slave mode, Sound-active mode, Manual control mode |
| Channel mode               | Compact mode 10CH, Standard mode 11CH                                                                   |
| Casing material            | V0 flame retardant ABS                                                                                  |
| Power connector            | 1 power input connector                                                                                 |
| Signal connector           | 1 RJ45 network input connector, 1 RJ45 network output connector                                         |
| Operating temperature      | -10°C ~ 45°C                                                                                            |
| IP rating                  | Ip20                                                                                                    |
| Product dimensions (L×W×H) | 233×233×175mm                                                                                           |
| Package dimensions (L×W×H) | 280×238×243mm (carton)                                                                                  |
| Package gross weight       | 2.1kg                                                                                                   |
| Product net weight         | 1.45kg                                                                                                  |