



Moving Head Beam Light

TL-SL111



Feature

- * Optics: high-precision glass optical lens (6-layer coating), multi-level optical lens group electronic focusing, linear magnification function.
- * Color wheel: 13 color gels + 1 white light, two-way rainbow effect, adjustable speed, flexible positioning function.
- * Gobo system: 1 fixed gobo wheel: 13 fixed gobos + 1 white light, one-way flowing effect, adjustable speed, flexible positioning function. 1 rotatable gobo wheel: 9 gobos + white circle, with pattern dithering and pattern flexible positioning function, pattern outer diameter:
- * Prism: 1 eight-sided rotating prism + 1 mirror array, the prism rotates forward and reverse, and the speed is adjustable.
- * Strobe: double-chip strobe 0.5-14 times/sec, support synchronous, asynchronous and random strobe modes, and adjustable speed.
- * Atomization: 1 independent atomization effect, the light spot is soft and natural.
- * Scanning range: X-axis 540°/630°/2.5 S, Y-axis 270°/1.5 S, resolution: 8Bit/16Bit.
- * Display interface: adopt wide-screen 2.8-inch LCD display interface in Chinese and English.
- * Intelligent heat dissipation: using wind direction drainage and temperature intelligent monitoring technology, according to the temperature of different positions of the lamp, the cooling fans in different parts of the lamp are automatically driven to effectively cool the lamp components.
- * Precise positioning: The three-phase stepper motor has a magnetic encoder positioning function and precise X.Y. scanning positioning.

Specification

| | |
|----------------------|--|
| Input voltage | AC110V-240V 50/60Hz , 470W |
| Ballast | Electronic ballast |
| Light source | PHILIPS 280 |
| Average lifespan | 2000H |
| Color temperature | 8500K |
| Beam angle | 3°-12°, Wash/15°-32° |
| Control mode | DMX512 (ART-NET/RDM/DMX wireless, optional) |
| Channel | 16/23 channels |
| Fixture material | High temperature resistant plastic + molded alloy material |
| Protection class | Ip30 |
| Fixture size (L×W×H) | 368×240×592mm |
| Package size (L×W×H) | 470×430×565mm |
| Net weight | 22.3kg |
| Gross weight | 19.8kg |